

County Surveyor's Record, Douglas County, Oregon

16771

Dependent Resurvey, Portion of Subdivisional Lines
T. 32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	N. 0° 21' W., bet. secs. 29 and 30.
	Ascend 120 ft. over SW. slope, through scattering timber and dense undergrowth, across logged area.
7.15	Divide bet. Bull Run Creek and Starvout Creek, bears NW. and SE., also dirt road, 15 lks. wide, bears same; desc. 225 ft. over NE slope.
20.09	Point for the S. 1/16 sec. cor. of secs. 29 and 30.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	S 1/16 S 30 S 29 1979
	from which
	A fir, 24 ins. diam., bears S. 36 1/2° E., 14 1/2 lks. dist., mkd. S 1/16 S29 BT.
	A fir, 6 ins. diam., bears N. 80 1/2° W., 42 1/4 lks. dist., mkd. S 1/16 S30 BT.
	Descend 10 ft. over NE slope.
23.10	Spur, slopes NE.; desc. 315 ft. over NW slope.
35.40	Low spur, slopes NW.; desc. 115 ft. over N. slope.
39.10	Gravelled road, 25 lks. wide, bears N. 60° E. and N. 60° W., in curve.
40.18	The 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground with brass cap mkd.
	1/4 S 30 S 29 T 32 S R 4 W 1959
	from which the remains of an original bearing tree
	A roothole, bears S. 68° W., 64 lks. dist. alongside of which is lying a fir, 24 ins. diam., no marks visible.
	and a bearing tree mkd. by Thielsen
	A fir, 29 ins. diam., bears N. 88 1/2° E., 60 lks. dist., with healed blaze. (Record, S. 88° E.)
	and a bearing tree mkd. by Ronald A. Brandt, Registered Land Surveyor, No. 841, in 1970
	A fir, 10 ins. diam., bears N. 10° W., 53 1/2 lks. dist., with healed blaze.
	—————
	N. 0° 29' E., beginning new measurement.
	Descend 20 ft. over NE. slope.
0.60	Ravine, drains NW.; asc. 14 ft. over SW. slope.