

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of S. Bdy.,
 (Fifth Standard Parallel South)
 T. 22 S., R. 8 W., Willamette Meridian, Oregon

16778

CHAINS	
	<p>Beginning at the cor. of secs. 31 and 32 only, on the S. bdy. of the Tp., perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1963, redescribed by Brooks and Jelley in 1963-65, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 16 ins. above ground, with iron cap mkd.</p>
	<p>BLM <u>S 31 S 32</u> S 6 1963</p>
	<p>from which an original bearing tree</p> <p style="padding-left: 40px;">A fir, 63 ins. diam., bears N. 70° W.; 25 lks. dist., with marks S3 R8W T visible on bark blaze. (Record and to face, 21 lks.)</p> <p>and a bearing free mkd. by Godfrey</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 39° E., 48 lks. dist., with healed blaze. (Record, N. 38° E.)</p> <p>From this point, the closing cor. of secs. 5 and 6, T. 23 S., R. 8 W., bears S. 89° 37' E., 1.47 chs. dist., described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 23 S., R. 8 W., executed concurrently under this same group.</p> <p>N. 89° 59' W., on the S. bdy. of sec. 31 marking and blazing the true line.</p> <p>Asc. 80 ft. over SE. slope, through moderate timber and undergrowth.</p>
5.40	Top of ascent, slopes SE.; desc. 15 ft. over SW. slope.
6.80	Ravine, drains S. 10° W.; asc. 150 ft. over SE. slope.
18.30	Point for the E. 1/16 sec. cor. of sec. 6 only, T. 23 S., R. 8 W., described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 23 S., R. 8 W., executed concurrently under this same group.
	Asc. 165 ft. over SE. slope.
19.05	Bridge Road, gravelled, 25 lks. wide bears N. 20° W. and S. 20° E.
28.10	Spur, slopes S.; desc. 220 ft. over SW. slope.
35.60	Lutzinger Creek Road, gravelled, 25 lks. wide, bears N. 50° W. and S. 10° E. in a curve.
38.07	Point for the 1/4 sec. cor. of sec. 6 only, T. 23 S., R. 8 W., described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 23 S., R. 8 W., executed concurrently under this same group.
	Desc. 10 ft. over SW. slope.
39.00	Ravine, drains S. 45° W.; asc. 10 ft. over SE. slope.
39.49	Point for the 1/4 sec. cor. of sec. 31 only, at proportionate dist.; there is no remaining evidence of the original cor.