

County Surveyor's Record, Douglas County, Oregon

16785

T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

States Coast and Geodetic Survey triangulation station "BUCK MOUNTAIN, 1942", located in section 10, is as follows:

Latitude: 47° 55' 40.7" N. Longitude: 123° 30' 20.2" W.

Dependent Resurvey of a Portion of the East Boundary,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the survey
by Addison R. Flint, U.S. Deputy Surveyor, in 1855)

Beginning at the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

COUNTY SURVEYOR'S OFFICE

T 30 S	T 30 S
S 1	S 6
S 12	S 7
R 7 W	R 6 W
1963	

from which the remains of the original bearing trees

A madrone, 37 ins. diam., bears N. 49° E., 106 lks. dist., with fragmentary scribe marks visible on open blaze.

A madrone, 36 ins. diam., bears S. 82° E., 125 lks. dist., with fragmentary scribe marks visible on bark blaze.

A madrone stub, 20 ins. diam., bears S. 3° W., 63 lks. dist., with fragmentary scribe marks visible on decayed blaze.

A root hole, bears N. 45° W., 16 lks. dist., with a down pine, 36 ins. diam., lying alongside, No marks visible.

and bearing trees mkd. by Byron in 1963

A white fir, 16 ins. diam., bears N. 81° E., 8 1/2 lks. dist., with healed blaze.

A fir, 13 ins. diam., bears S. 25° E., 34 lks. dist., with healed blaze.

A white fir, 19 ins. diam., bears S. 58° W., 32 1/2 lks. dist., with healed blaze.

N. 1° 08' E., bet. secs. 1 and 6 marking and blazing the true line.

Ascend 10 ft. over SE. slope, through scattering timber and light undergrowth.

1.50

Dirt road, 15 lks. wide, bears E. and W.