Dependent Resurvey, Portion of E. Bdy.,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
1.60	Ridge, bears E. and W.; desc. 390 ft. over broken NE. slope.
13.95	Ravine, drains N. 45° E.; asc. 225 ft. over SE. slope.
17.10	Spur, slopes N. 65° E.; desc. 15 ft. over broken NE. slope.
19.27	The S 1/16 sec. cor. of secs. 1 and 6, established and recorded by Howard W. Johnstone, Registered Land Surveyor No. 498, in 1977, and is accepted as the cor., monumented with an iron rod, 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with aluminum cap mkd. S 1/16 S 1 S 6 from which bearing trees mkd. by Johnstone A fir, 7 ins. diam., bears S. 12 1/2° E., 30 lks. dist., with fragmentary scribe marks visible on open blaze. A fir, 7 ins.diam., bears S. 37 1/2° W., 30 lks. dist., with scribe marks S. 1/16 BT, visible on open blaze.
	N. 1° 08' E., beginning new measurement. Descend 160 ft. over NE. slope.
7.45	Creek, 5 lks. wide, course N. 30° W.; asc. 200 ft. over SW. slope.
19.24	The 1/4 sec. cor. of secs. 1 and 6, reestablished by proportionate measurement and recorded by Howard W. Johnstone, Registered Land Surveyor No. 498, in 1977, and is accepted as the best available evidence of the position of the original cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 8 ins. above ground, with aluminum cap mkd. 1/4 S1 | 6 from which bearing trees mkd. by Johnstone A fir, 8 ins. diam., bears N. 63° E., 28 lks. dist., with scribe marks 1/4 S6 BT, visible on open blaze. A fir, 10 ins. diam., bears N. 14° W., 15 lks. dist., with scribe marks 1/4 S1 BT., visible on open blaze.
	N. 1° 09' E., beginning new measurement. Ascend 20 ft. over SW. slope.
1.30	Spur, slopes W.; desc. 350 ft. over NW. slope.
12.65	Thompson Creek,5 lks wide, course S. 40° W.; asc. 190 ft. over SE. slope.