

County Surveyor's Record, Douglas County, Oregon

16787

Dependent Resurvey, Portion of E. Bdy.,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

19.255

Point for the N. 1/16 sec. cor. of secs. 1 and 6.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16
S 1 | S 6
1980

from which

A fir, 8 ins. diam., bears N. 57 1/2° E., 39 1/2 lks. dist., mkd. N 1/16 S6 BT.

A fir, 6 ins. diam., bears S. 52° W., 10 1/2 lks. dist., mkd. N 1/16 S1 BT.

Ascend 35 ft. over SE. slope.

21.25

Spur, slopes S. 75° E.; desc. 65 ft. over NE. slope.

26.35

Creek, 3 lks. wide, course S. 45° E.; asc. 130 ft. over SW. slope.

35.20

Creek, 1 lk. wide, course S. 50° W.; asc. 55 ft. over SE. slope.

38.51

The cor. of Tps. 29 and 30 S., Rs. 6 and 7 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 29 S
R 7 W R 6 W
S 36 | S 31
S 1 | S 6
T 30 S
1968

from which bearing trees mkd. by Mensch in 1905

A white oak, 28 ins. diam., bears N. 81 1/2° E., 22 lks. with healed blaze. This tree was rescribed S31 by Markham in 1956.

A white oak, 22 ins. diam., bears S. 20 1/2° E., 50 lks. dist. with scribe marks B visible on partially open blaze. This tree was rescribed S 6 BT by Markham in 1956.

and bearing trees mkd. by J. H. Markham, Registered Engineer No. 2880, in 1956

A madrone, 32 ins. diam., bears N. 3° E., 80 1/2 lks. dist., with fragmentary scribe marks visible on partially open blaze.

A white oak, 16 ins. diam., bears S. 31 1/4° E., 48 1/2 lks. dist., with healed blaze.

A white oak, 27 ins. diam., bears N. 50° W., 267 lks. dist., fragmentary scribe marks visible on partially open blaze.

and a bearing tree mkd. by Roseberry in 1968