

County Surveyor's Record, Douglas County, Oregon

16788

Dependent Resurvey, Portion of E. Bdy.,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A fir, 8 ins. diam., bears S. 49° W., 18 1/2 lks.
dist., with healed blaze.

From this point, a cor. established and recorded by James W. Byron, Deputy County Surveyor, in 1962, bears S. 23° 30' E., 0.025 chs. dist., monumented with an iron post, firmly set, projecting 12 ins. above ground, with brass cap mkd. County Surveyor's Office T29S R6W R7W S36 S31 S1 S6 T30S 1962.

Land, mountainous.
Soil, rocky clay loam.
Timber, fir, hemlock, cedar, maple, oak, pine, alder, madrone, and chinquapin; undergrowth, poison oak, salal, rhododendron, Oregon grape, vine maple, ferns, and grasses.

Dependent Resurvey of
a Portion of the Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the survey
by William H. Byars, U.S. Deputy Surveyor, in 1872)

From the 1/4 sec. cor. of secs. 1 and 12, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1964, monumented with an iron post, 1 1/4 ins. diam., firmly set projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYOR'S OFFICE
T 30 S R 7 W
1/4 S 1
S 12
1964

from which the original bearing trees

A fir, 72 ins. diam., bears N. 50° E., 24 lks.
dist., with fragmentary scribe marks visible on bark blaze.

A black oak, 30 ins. diam., bears S. 40° W., 28 lks.
dist., with healed blaze.

and bearing trees mkd. by Tracy

A fir, 14 ins. diam., bears N. 20° E., 63 lks.
dist. with healed blaze.

A fir, 16 ins. diam., bears S. 2 1/2° E., 48 lks.
dist., with healed blaze.

N. 89° 51' W., bet. secs. 1 and 12, marking and blazing the true line.

Descend 405 ft. over broken SW. slope, through scattering timber and light undergrowth.

19.905

Point for the W 1/16 sec. cor. of secs. 1 and 12.