

County Surveyor's Record, Douglas County, Oregon

16789

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

W 1/16 $\frac{S 1}{S 12}$
1980

from which

A yew, 8 ins. diam., bears N. 23° E., 73 lks.
dist., mkd. W 1/16 S 1 BT.

A cedar, 12 ins. diam., bears S. 86 1/2° E., 28 lks.
dist., mkd. W. 1/16 S12 BT.

Cor. is located in creek, 10 lks. wide, course N. 10° E.

Ascend 90 ft. over SE. slope.


24.50 Spur, slopes N.; desc. 180 ft. over NW. slope.

30.65 A seasonal waterfall, course N. 50° W.; asc. 100 ft. over NW. slope.

36.65 Spur, slopes N. 30° W.; desc. 15 ft. over NW. slope.

39.81 The cor. of secs. 1, 2, 11, and 12, perpetuated and recorded by J. H. Markham, Registered Engineer No. 2880, in 1956, and further perpetuated and recorded by Francis L. Ingram, County Surveyor, in 1978, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYOR'S OFFICE



from which the remaining original bearing trees

A white oak, 11 ins. diam., bears N. 20° E., 50 lks.
dist., with healed blaze. (Record, 54 lks.)

A pine, 52 ins. diam., bears S. 70° E., 96 lks.
dist., with scribe marks S12 visible on open
blaze.

and bearing trees mkd. by Markham

An oak, 8 ins. diam., bears N. 73° E., 52 lks.
dist., with healed blaze.

A cedar, 13 ins. diam., bears S. 50° E., 18 lks.
dist., with fragmentary scribe marks visible on
open blaze.

A cedar, 15 ins. diam., bears N. 83° W., 12 lks.
dist., with fragmentary scribe marks visible on
open blaze.

A cedar, 15 ins. diam., bears N. 27° W., 8 1/2 lks.
dist., with fragmentary scribe marks visible on
open blaze.

and a bearing tree mkd. by Ingram