

County Surveyor's Record, Douglas County, Oregon

16792

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A fir, 13 ins. diam., bears S. 23° W., 29 1/2 lks. dist., mkd. T30S R7W S2 BT.

A fir, 9 ins. diam., bears N. 6 1/2° W., 42 lks. dist., mkd. T29S R7W S35 BT.

Land, mountainous.
Soil, rocky clay loam.
Timber, fir, hemlock, cedar, maple, oak, madrone, alder, and chinquapin; undergrowth, salal, Oregon grape, vine maple, rhododendron, poison oak, ferns, and grasses.

From the cor. of secs. 26, 27, 34, and 35, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1962, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

COUNTY SURVEYOR'S OFFICE

T 30 S	
S 27	S 26
S 34	S 35
R 7 W	
1962	

FURTHER
EVIDENCE
1962

from which the remains of an original bearing tree
A fir snag, 24 ins. diam., bears N. 75° W., 23 lks. dist., no marks remaining on decayed blaze.

and bearing trees mkd. by Byron in 1962

A fir snag, 15 ins. diam., bears S. 49 3/4° E., 127 lks. dist., with healed blaze.

A live oak, 25 ins. diam., bears S. 64 1/2° W., 26 lks. dist., with fragmentary scribe marks visible on partially open blaze.

A live oak, 8 ins. diam., bears N. 20° W., 82 1/2 lks. dist., with scribe marks S27 CS BT visible on partially open blaze.

No other suitable trees available.

N. 1° 16' E., bet. secs. 26 and 27.

Descend 290 ft. over NE. slope, through heavy timber and dense undergrowth.

13.75 Gravelled road, 30 lks. wide, bears N. 45° W. and S. 45° E.

15.00 Ravine, drains S. 70° E.; asc. 70 ft. over SW. slope.

18.80 Gravelled road, 30 lks. wide, bears N. 30° E. and S. 30° W.

20.175 Point for the S 1/16 sec. cor. of secs. 26 and 27.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 40 ins. in the ground, with top 12 ins. below the surface of road, with brass cap mkd.