

County Surveyor's Record, Douglas County, Oregon

16793

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	S 1/16 S 27 S 26 1980
	from which
	A fir, 10 ins. diam., bears S. 41° E., 52 lks. dist. mkd. S 1/16 S26 BT.
	An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument bears S. 50° W., 46 lks. dist., with brass cap mkd. S 1/16 S27 RM 1980 with an arrow pointing to the cor.
	Cor. is located on W. edge of gravelled road, 30 lks. wide, bears N. 5° E. and S. 30° W. in curve.
	Ascend 25 ft. over SE. slope, along road.
22.50	Leave road, bears N. 10° W. and S. 5° E.
23.25	Top of ascent, slopes E.; desc. 100 ft. over NE. slope.
26.80	Creek, 6 lks. wide, course S. 30° E.; asc. 300 ft. over SW. slope.
40.35	The 1/4 sec. cor. of secs. 26 and 27, determined at record bearing and distance from the remaining original bearing tree
	A pine, 28 ins. diam., bears S. 35° E., 194 lks. dist., with fragmentary scribe marks visible on partially opened blaze.
	At the corner point
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.
	T 30 S R 7 W 1/4 S 27 S 26 1980
	from which new bearing trees
	A pine, 15 ins. diam., bears S. 25 1/2° E., 146 lks. dist., mkd. 1/4 S26 BT.
	A fir, 10 ins. diam., bears S. 4 1/2° W., 116 lks. dist., mkd. 1/4 S27 BT.

	N. 0° 58' E., beginning new measurement.
	Ascend 55 ft. over broken SW. slope.
4.40	Ravine, drains N. 40° W.; asc. 120 ft. over SW. slope.
11.30	Spur, slopes W.; desc. 225 ft. over NW. slope.