

County Surveyor's Record, Douglas County, Oregon

16794

Dependent Resurvey, Portion of Subdivisional Lines
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

21.40

Creek, 1 lk. wide, course S. 40° W.; asc. 5 ft. over broken SW. slope.

24.20

Doe Creek, 10 lks. wide, course S. 10° W.; asc. 5 ft. over S. slope.

40.62

Point for the cor. of secs. 22, 23, 26, and 27, at proportionate distance; there is no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T	30	S	R	7	W
	S	22		S	23
	S	27		S	26
	1980				

from which

A cedar, 26 ins. diam., bears N. 43° E., 391 lks. dist., mkd. T30S R7W S23 BT.

A cedar, 5 ins. diam., bears S. 63 1/4° E., 239 lks. dist., mkd. X BT.

A fir, 19 ins. diam., bears S. 66° W., 174 lks. dist., mkd. T30S R7W S27 BT.

A fir, 6 ins. diam., bears N. 43 1/4° W., 71 lks. dist., mkd. T30S R7W S22 BT.

From this point, the 1/4 sec. cor. of sec. 23 and 26, bears S. 89° 36' E., 39.86 chs. dist., determined at record bearing and distance from the remains of the original bearing trees

A root crown, bears N. 60° E., 64 lks. dist., with a down fir alongside 16 ins. diam., with scribe marks 1/4 S visible on opened blaze.

A pine root crown, 25 ins. diam., bears S. 70° W., 32 lks. dist., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T	30	S	R	7	W
	1/4	S	23		
		S	26		
	1982				

from which new bearing trees

A fir, 8 ins. diam., bears N. 45° E., 90 lks. dist., mkd. 1/4 S23 BT.

A cedar, 6 ins. diam., bears S. 66 1/4° W., 27 lks. dist., mkd. 1/4 S26 BT.

From this same point, the 1/4 sec. cor. of secs. 22 and 23 bears N. 3° 36' E., 40.69 chs. dist., perpetuated and recorded by Romanso E. Ware, Registered Land Surveyor, No. 1005, in 1975, monumented with an iron pipe, 1 1/4 ins.