

County Surveyor's Record, Douglas County, Oregon

16795

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p>diam., firmly set, projecting 10 ins. above ground, from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A root hole, bears N. 22° W., 34 lks. dist., with a down pine alongside, 20 ins. diam., with scribe marks BT visible on decayed blaze.</p> <p>and bearing trees mkd. by Ware</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 52° E., 85 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 52° W., 35 1/2 lks. dist., with healed double blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T 30 S R 7 W 1/4 S 22 S 23 1982</p> </div> <p>Reset the iron pipe alongside the iron post.</p> <p>Land, mountainous. Soil, rocky clay loam. Timber, fir, hemlock, cedar, maple, oak, madrone, chinquapin, and alder,; undergrowth, salal, Oregon grape, poison oak, vine maple, rhododendron, hazel, ferns, and grasses.</p>
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89° 16' W., bet. secs. 27 and 34.</p> <p>Ascend 60 ft. over NE. slope, through heavy timber and dense undergrowth.</p> <p>2.30 Ridge, bears N. 50° W. and S. 50° E.; desc. 145 ft. over SW. slope.</p> <p>6.80 Ravine, drains S. 20° W.; asc. 50 ft. over SE. slope.</p> <p>10.85 Spur, slopes S.; desc. 350 ft. over SW. slope.</p> <p>19.895 Point for the E 1/16 sec. cor. of secs. 27 and 34.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>E 1/16 $\frac{S\ 27}{S\ 34}$ 1980</p> </div> <p>from which</p> <p style="padding-left: 40px;">A madrone, 14 ins. diam., bears N. 13° W., 44 1/2 lks. dist., mkd. E 1/16 S27 BT on bark blaze.</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears S. 59° W., 13 1/2 lks. dist., mkd. E 1/16 S34 BT.</p>