

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

16796

CHAINS	
	Descend 55 ft. over SW. slope.
24.15	Buck Creek, 10 lks. wide, course S. 10° E.; asc. 240 ft. over NE. slope.
32.80	Ravine, drains N. 10° E.; asc. 120 ft. over NE. slope.
39.79	The 1/4 sec. cor. of secs. 27 and 34, perpetuated and recorded by Francis L. Ingram, County Surveyor, in 1975, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.
	<p>COUNTY SURVEYOR'S OFFICE T 30 S R 7 W 1/4 $\frac{S\ 27}{S\ 34}$ 1975</p> <p style="text-align: right; font-size: small;"><i>FD OK BY [unclear] 5/17/81</i></p>
	from which the remains of the original bearing trees
	A fir snag, 42 ins. diam., bears N. 10° E., 37 lks. dist., with axe marks visible on open blaze.
	A root hole, bears S. 60° E., 10 lks. dist., with a fir, 60 ins. diam., lying downhill 30 ft. with scribe marks 1/4 S visible on decayed bark blaze.
	and bearing trees mkd. by Ingram
	A fir, 9 ins. diam., bears N. 60 1/2° W., 57 lks. dist., with fragmentary scribe marks visible on open blaze.
	A fir, 10 ins. diam., bears S. 36° W., 38 lks. dist., with fragmentary scribe marks visible on open blaze.

	N. 89° 47' W., beginning new measurement.
	Ascend 700 ft. over NE. slope.
19.29	Point for the W 1/16 sec. cor. of secs. 27 and 34.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>W 1/16 $\frac{S\ 27}{S\ 34}$ 1980</p> <p style="text-align: right; font-size: small;"><i>FD OK BY [unclear] 5/17/81</i></p>
	from which
	A fir, 4 ins. diam., bears N. 66 3/4° W., 13 1/2 lks. dist., mkd. X BT.
	A fir, 6 ins. diam., bears S. 25° E., 18 1/2 lks. dist., mkd. W 1/16 S34 BT.
	Ascend 40 ft. over SE. slope.
20.30	Spur ridge, bears N. and S., slopes S.; asc. 370 ft. along broken S. slope.
36.90	Ridge, bears N. and S.; desc. 5 ft. over SW. slope.