

# County Surveyor's Record, Douglas County, Oregon

16799

Subdivision of Section 27,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
12.95	Spur, slopes E.; desc. 5 ft. over NE. slope.
15.75	Buck Creek, 10 lks. wide, course S. 45° E.; asc. 125 ft. over SW. slope.
20.105	Point for the center S 1/16 sec. cor. of sec. 27.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <p>C S 1/16   S 27 C 1980</p> </div> <p>from which</p> <p style="margin-left: 40px;">A rock outcrop, 8 x 4 x 4 ft. high, bears S. 75 1/2° E., 6 lks. dist., mkd. X BO on ledge 1 ft. up.</p> <p style="margin-left: 40px;">A cedar, 8 ins. diam., bears N. 38 1/2° W., 54 lks. dist., mkd. CS 1/16 S27 BT.</p> <p>Ascend 30 ft. over SW. slope.</p>
20.90	Spur, slopes W.; desc. 35 ft. over NW. slope.
24.00	Buck Creek, 10 lks. wide, course S. 50° W.; asc. 55 ft. over broken SE. slope.
29.65	Buck Creek, 10 lks. wide, course S. 40° E.; asc. 215 ft. over SW. slope.
40.21	Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E. and W. center line.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <p>T 30 S R 7 W C 1/4 S 27 1980</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 11 ins. diam., bears S. 15° E., 66 lks. dist., mkd. C 1/4 S27 BT.</p> <p style="margin-left: 40px;">A basalt boulder, in place, 5 x 4 x 3 ft. high, bears N. 20° W., 4 lks. dist., mkd. X BO on face.</p> <p>Ascend 205 ft. over SW. slope.</p>
46.60	Spur, slopes S. 60° W.; desc. 95 ft. over NW slope.
55.70	Creek, 1 lk. wide, course N. 45° W.; asc. 145 ft. over S. slope.
60.05	Spur, slopes S. 40° W.; asc. 35 ft. over SW. slope.
64.70	Spur, slopes W.; desc. 60 ft. over NW. slope.
66.90	Ravine, drains S. 85° W.; asc. 75 ft. over SW. slope.