

County Surveyor's Record, Douglas County, Oregon

16800

Subdivision of Section 27,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
70.50	Spur, slopes W.; desc. 70 ft. over NW. slope.
76.80	Dirt road, 15 lks. wide, bears N. 55° E., and S. 55° W.
78.10	Ravine, drains W.; asc. 10 ft. over SW. slope.
79.73	The 1/4 sec. cor. of secs. 22 and 27.
<p>From the 1/4 sec. cor. of secs. 26 and 27.</p> <p>N. 89° 28' W., on the E. and W. center line of sec. 27.</p> <p>Descend 105 ft. over SW. slope, through scattering timber and dense undergrowth.</p>	
4.30	Doe Creek, 8 lks. wide, course S. 10° W.; asc. 565 ft. over SE. slope.
5.40	Gravelled road, 30 lks. wide, bears N. 30° E. and S. 30° W.
19.945	Point for the center E 1/16 sec. cor. of sec. 27.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="display: flex; align-items: center; justify-content: center;"> <div style="margin-right: 10px;">C</div> <div style="text-align: center;"> <p>E 1/16</p> <hr style="width: 100%; border: 0.5px solid black;"/> <p>S 27</p> <p>1980</p> </div> <div style="margin-left: 10px;">C</div> </div>
	from which
	A fir, 8 ins. diam., bears N. 81° E., 39 lks. dist., mkd. CE 1/16 S27 BT.
	A pine, 4 ins. diam., bears S. 75° W., 18 lks. dist., mkd. X BT.
	Ascend 35 ft. over SE. slope.
22.30	Spur, slopes N. 40° E.; asc. 40 ft. over NE. slope.
24.95	Top of ascent, slopes N; desc. 350 ft. over SW. slope.
39.89	The center 1/4 sec. cor. of sec. 27.
	Descend 180 ft. over W. slope.
48.00	Buck Creek, 4 lks. wide, course S. 35° E.; asc. 295 ft. over SE. slope.
63.40	Top of ascent, slopes N.; desc. 45 ft. over broken NW. slope.
69.70	Creek, 1 lk. wide, course N. 25° E.; asc. 25 ft. over SE. slope.
71.50	Top of ascent, slopes N.; desc. 95 ft. over NW. slope.
78.80	Creek, 3 lks. wide, course N. 60° E.; asc. 60 ft. over NE. slope.
80.06	The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.