

# County Surveyor's Record, Douglas County, Oregon

16801

Subdivision of Section 27,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

1/4      T 30 S  
          S 28 | S 27  
          B L M    1965  
          R 7 W  
          1965

from which a bearing tree mkd. by James W. Byron, County Surveyor in 1965

A fir, 9 ins. diam., bears S. 4° E., 42 1/2 lks. dist., with healed blaze.

and a new bearing tree

A sawed fir stump, 23 ins. diam., bears S. 22° W., 50 1/2 lks. dist., mkd. 1/4 S28 BT.

From the center E 1/16 sec. cor. of sec. 27.

N. 1° 02' E., on the N. and S. center line of the NE 1/4 of sec. 27.

Descend 245 ft. over NE. slope.

14.15      Ravine, drains N. 70° E.; asc. 95 ft. over S. slope.

17.90      Spur, slopes S. 85° E.; desc. 90 ft. over NE. slope.

23.45      Head of ravine, drains S. 60° E.; asc. 20 ft. over SE. slope.

25.05      Spur, slopes S. 75° E.; desc. 55 ft. over NE. slope.

27.85      Ravine, drains S. 40° E.; asc. 110 ft. over S. slope.

32.25      Spur, slopes S. 70° E.; desc. 210 ft. over NE slope.

40.07      The E 1/16 sec. cor. of secs. 22 and 27.

From the E 1/16 sec. cor. of secs. 27 and 34.

N. 1° 12' E., on the N. and S. center line of the SE 1/4 of sec. 27.

Ascend 655 ft. over SW. slope.

20.135      Point for the SE 1/16 sec. cor. of sec. 27 at intersection with the E. and W. center line of the SE 1/4.

Set an iron post, 28 ins. long 2 1/2 ins. diam., 24 ins in the ground with brass cap mkd.

SE 1/16    S 27  
          1980

from which

A white oak, 36 ins. diam., bears N. 30° E., 20 1/2 lks. dist., mkd. SE 1/16 S27 BT.

A fir, 20 ins. diam., bears S. 31 3/4° W., 35 1/2 lks. dist., mkd. SE 1/16 S27 BT.