

# County Surveyor's Record, Douglas County, Oregon

16805

Dependent Resurvey, Portion of Subdivisional Lines  
T. 30 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

(Restoring the survey by Nathaniel Ford,  
U. S. Deputy Surveyor, in 1854,  
the resurvey by William Thiel,  
U. S. Deputy Surveyor, in 1889  
the resurvey by William F. Briggs,  
U. S. Deputy Surveyor, in 1891,  
and the survey by William M. Bushey,  
U. S. Deputy Surveyor, in 1893)

Beginning at the cor. of secs. 25, 26, 35, and 36, perpetuated and recorded by Robert M. Thompson, Registered Engineer, No. 3683, in 1957, and further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron pipe, 1/2 in. diam., firmly set, projecting 6 ins. above ground, from which a bearing tree mkd. by Thiel:

A fir, 29 ins. diam., bears S. 46° W., 26 lks. dist., with healed blaze.

and a bearing tree mkd. by Thompson

A madrone, 12 ins. diam., bears N. 58° E., 41 lks. dist., with scribe marks S25 BT visible on partially healed double blaze.

and bearing trees mkd. by Byron

A fir, 15 ins. diam., bears S. 31 1/2° E., 79 lks. dist., with healed blaze.

A fir, 10 ins. diam., bears N. 29 1/4° W., 33 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 30 S R 4 W  
S 26 | S 25  
S 35 | S 36  
1981

Reset iron pipe alongside iron post.

N. 0° 28' W., bet. secs. 25 and 26, marking and blazing the true line.

Descend 270 ft. over broken NE. slope, through heavy timber and dense undergrowth.

17.60 Ravine, drains N. 70° W.; asc. 65 ft. over SW. slope.

19.80 Spur, slopes N. 55° W.; desc. 15 ft. over NE. slope.

20.195 Point for the S 1/16 sec. cor. of secs. 25 and 26.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

S 1/16  
S 26 | S 25  
1981