

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines **16806**  
T. 30 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p style="margin-left: 40px;">A fir, 5 ins. diam., bears S. 78 1/4° E., 8 1/2 lks. dist., mkd. X BT.</p> <p style="margin-left: 40px;">A fir, 16 ins. diam., bears S. 68 1/2° W., 21 1/2 lks. dist., mkd. S 1/16 S26 BT.</p> <p>Descend 425 ft. over NE. slope.</p>
31.80	Gravelled road, 15 lks. wide, bears N. 50° W. and S 65° E.
38.05	Gravelled road, 15 lks. wide, bears N. 30° E. and S. 40° W.
38.80	Intersect the S. side of a wood frame house, 52 x 35 ft., the SE. corner bears N. 65° E., 18 lks. dist., the long side bears N. 65° E. and S. 65° W.
40.39	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 30 S R 4 W 1/4 S 26   S 25 1981</p> <p style="font-size: small; margin: 0;"><i>FIND AIX 9/92 BY BROWN M115-57</i></p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 12 ins. diam., bears S. 24° E., 269 lks. dist., mkd. 1/4 S25 BT.</p> <p style="margin-left: 40px;">A cedar, 13 ins. diam., bears S. 73° W., 307 lks. dist., mkd. 1/4 S26 BT.</p> <p>Corner is located in gravelled driveway, 15 lks. wide, bears N. 30° E. and S. 30° W.</p> <p>Descend 25 ft. over river bottom land.</p>
46.05	Left bank of South Umpqua River, bears N. 80° W. and S. 30° E., course N. 80° W.
48.25	Right bank of South Umpqua River, bears N. 75° W. and S. 65° E.; continue over nearly level river bottom land.
72.95	Right bank of South Umpqua River, bears N. 25° E. and S. 20° W., course N. 25° E.
75.35	Left bank of South Umpqua River, bears N. 70° E. and S. 70° W.; asc. 5 ft. over gravel bar.
80.78	<p>The cor. of secs. 23, 24, 25, and 26, determined at record bearing and distance from a direct tie to the NW. cor. of Donation Land Claim No. 51, hereinafter described.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>