

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey Portion of Subdivisional Lines, **16810**  
T. 30 S., R. 4 W., Willamette Meridain, Oregon

CHAINS

T 30 S R 4 W

1/4  $\frac{S\ 23}{S\ 26}$

1981

from which

A fir, 8 ins. diam., bears N. 51 1/4° E., 11 lks.  
dist., mkd. 1/4 S23 BT.

A fir, 10 ins. diam., bears S. 8° E., 20 lks.  
dist., mkd. 1/4 S26 BT.

Descend 415 ft. over broken NW. slope.

70.20 Creek, 2 lks. wide, course N. 35° E.; asc. 315 ft. over SE. slope.

79.80 Gravelled road, 25 lks. wide, bears N.25° E. and S. 25° W.

80.20 The cor. of secs.22, 23, 26, and 27, perpetuated and recorded by John H. Markham, Registered Engineer No 2880, in 1958, and further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an axle, 2 1/2 ins. diam., firmly set, projecting 14 ins. above ground, from which the remains of bearing trees mkd. by Thiel:

A sawed fir stump, 30 ins. diam., bears N. 24° E.,  
26 lks. dist., with healed blaze.

A fir, 45 ins. diam., bears S. 79° W., 44 lks.  
dist., with healed blaze.

A sawed fir stump, 30 ins. diam., bears N. 29° W.,  
76 lks. dist., with healed blaze.

and the remains of bearing trees mkd. by Markham

A sawed madrone stump, 13 ins. diam., bears  
N. 28° E., 13 lks. dist., no marks visible.

A root hole, bears N. 58° W., 6 1/2 lks. dist., with  
a down fir alongside, 16 ins. diam., with  
healed double blaze.

A decayed madrone stump, size indeterminate, bears  
N. 29° W., 58 lks. dist., with scribe marks BT  
visible on decayed blaze.

and bearing trees mkd. by Byron

A madrone, 10 ins. diam., bears S. 83° W., 31 lks.  
dist., with healed double blaze.

A madrone, 10 ins. diam., bears N. 20° W., 33 lks.  
dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 30 S R 4 W

$\frac{S\ 22\ | S\ 23}{S\ 27\ | S\ 26}$

1981