

County Surveyor's Record, Douglas County, Oregon

16811

Dependent Resurvey, Portion of Subdivisional Lines,
T 30 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which new bearing trees</p> <p style="margin-left: 40px;">A fir, 28 ins. diam., bears N. 52 1/2° E., 221 lks. dist., mkd. T30S R4W R6W S23 BT.</p> <p style="margin-left: 40px;">A fir, 9 ins. diam., bears S. 51° E., 84 lks. dist., mkd. T30S R4W S26 BT.</p> <p style="margin-left: 40px;">Reset axle alongside iron post.</p> <p>Land, mountainous. Soil, rocky clay loam. Timber, pine, fir, cedar, yew, oak, ash, maple hemlock, alder, and madrone; undergrowth, salal, poson oak, fern. blackberry, salmonberry, thimbleberry, huckleberry, Oregon grape, hazel, arrowwood, vine maple, and young timber.</p>
	<p>N 1° 07' E., bet. secs. 22 and 23.</p> <p>Ascend 25 ft. over SE. slope, through heavy timber and dense undergrowth.</p>
8.15	<p>Spur, slopes N. 40° E.; desc. 440 ft. over broken NE. slope.</p>
12.20	<p>Gravelled road, 25 lks. wide, bears N. 70° W. and S. 70° E.</p>
19.48	<p>The S 1/16 sec. cor. of secs. 22 and 23, established and recorded by Burton W. Holt, Registered Land Surveyor No. 418, in 1978, and is accepted as the corner, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, with 2 ins. diam., aluminum cap mkd.</p> <div style="text-align: center; margin-left: 100px;"> <p>S 1/16 <i>FD. OK 10-93 R. BROWN</i> S 22 S 23 <i>M 119-7</i> 1978 RLS 418</p> </div> <p>from which bearing trees mkd. by Holt</p> <p style="margin-left: 40px;">A fir, 10 ins. diam., bears N. 33 1/2° E., 30 1/2 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 10 ins. diam., bears N. 59 3/4° W., 52 lks. dist., with healed blaze.</p> <p>From this point, a locally established corner bears S. 16° 12' W., 0.70 chs. dist., monumented with an axle, 2 ins. diam., firmly set, projecting 16 ins. above ground.</p>
19.47	<p>N. 1° 08' E., beginning new measurement.</p> <p>Descend 40 ft. over broken NE. slope, through scattering timber and moderate undergrowth.</p> <p>The 1/4 sec. cor. of secs. 22 and 23, perpetuated and re- corded by Floyd C. Frear, Deputy County Surveyor, in 1938, and further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron bar, 2 x 1/4 ins. firmly set, projecting 8 ins. above ground, from which the remaining original bearing tree:</p>