

County Surveyor's Record, Douglas County, Oregon

16814

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

40.69

Point for the 1/4 sec. cor. of secs. 10 and 11, determined by the method of irregular boundaries; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with broken clear glass at base, with brass cap mkd.

T 30 S R 4 W
1/4
S 10 | S 11
1981

from which

An oak, 15 ins. diam., bears S. 85 1/2° E., 128 1/2 lks. dist., mkd. 1/4 S11 BT.

A fir, 7 ins. diam., bears S. 58 1/2° W., 79 1/2 lks. dist., mkd. 1/4 S10 BT.

From this point, an iron pipe, 3/4 in. diam., firmly set, the top 3 ins. below surface of the ground, bears S. 58° 54' E., 0.865 chs. dist. This pipe is located 0.10 chs. W. of a corner of wire fences, extending N. 45° E., S., E., and W.

N. 0° 50' E., beginning new measurement.
Descend 135 ft. over broken NE. slope.

12.05

Woven wire fence, extends E. and W.

25.75

Days Creek Road, asphalt surfaced, 30 lks. wide, bears E. and W.

27.45

Days Creek, 20 lks. wide, course W.; asc. 35 ft. over SW. slope.

38.52

The cor. of secs. 2, 3, 10, and 11, determined at record bearing and distance from the remains of a bearing tree mkd. by Thiel:

A sawed fir stump, 45 ins. diam., bears N. 52° W., 202 lks. dist., with scribe marks BT visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 42 ins. in the ground, the top 14 ins. below surface, with brass cap mkd.

T 30 S R 4 W
S 3 | S 2
S 10 | S 11
1981

from which reference monuments

An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 25 1/4° E., 327 1/2 lks. dist., with brass cap mkd. T30S R4W S11 RM 1981 and an arrow pointing to the corner.

An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 78 3/4° W., 92 1/2 lks. dist., with brass cap mkd. T30S R4W S10 RM 1981 and an arrow pointing to the corner.