

County Surveyor's Record, Douglas County, Oregon

16815

Dependent Resurvey, Portion of Subdivisional Lines
T. 30 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 57 1/4° W., 114 lks. dist., with brass cap mkd. T30S R4W S3 RM 1981 and an arrow pointing to the corner.

Corner is located in cultivated field.

From this point, the 1/4 sec. cor. of secs. 2 and 11, bears S. 88° 24' E., 39.85 chs. dist., perpetuated and recorded by F. C. Frear, Deputy County Surveyor, in 1918, from original evidence no longer in existence, and further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.

*FND OK 10/92
R. BROWN M115-67*

COUNTY SURVEYORS OFFICE

	T 30 S	R
1/4	S 2	4
	S 11	W
	1963	

from which the remains of a bearing tree mkd. by Frear

A white oak, 25 ins. diam., bears N. 73° E., 201 lks. dist., with healed double blaze.

and reference monuments

An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45° E., 21 1/2 lks. dist., with brass cap mkd. 1/4 S11 RM 1981 and an arrow pointing to the corner.

An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 1° W., 13 lks. dist., with brass cap mkd. 1/4 S2 RM 1981 and an arrow pointing to the corner.

From this same point, the 1/4 sec. cor. of secs. 2 and 3 bears N. 0° 53' E., 37.81 chs. dist., perpetuated and recorded by F. C. Frear, Deputy County Surveyor, in 1919, from original evidence no longer in existence, further perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1949, and still further perpetuated and recorded by Robert M. Thompson, Registered Engineer No. 3683, in 1955, monumented with an iron pipe. 1 in. diam., firmly set, the top 1 in. below surface of the ground, from which a bearing tree mkd. by Markham:

A cedar, 25 ins. diam., bears S. 78 1/2° E., 38 lks. dist., with healed double blaze.

and a bearing tree mkd. by Thompson

A cedar, 23 ins. diam., bears S. 2 1/2° E., 46 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, flush with surface, with brass cap mkd.

	T 30 S R 4 W
	1/4
	S 3 S 2
	1981