

County Surveyor's Record, Douglas County, Oregon

16817

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

39.90

The 1/4 sec. cor. of secs. 3 and 10, perpetuated and recorded by F. C. Frear, Deputy County Surveyor, in 1918, further perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1957, and still further perpetuated and recorded by R. B. Kimberly, Deputy County Surveyor, in 1977, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S R 4 W

1/4

S 3

S 10

1977

from which the remaining original bearing tree

An oak, 20 ins. diam., bears N. 35° W., 77 lks. dist., with open blaze, no marks visible.
(Record, N. 32° W.)

and bearing trees mkd. by Markham

A white oak, 11 ins. diam., bears N. 35° E., 123 lks. dist., with healed double blaze.

A madrone, 16 ins. diam., bears N. 42° W., 131 lks. dist., with healed double blaze.

and a bearing tree mkd. by Kimberly (sic)

A black oak, 15 ins. diam., bears N. 79° W., 84 lks. dist., with healed double blaze.

Corner is located in N. edge of grain field, edge bears N. 80° E. and S. 80° W.

N. 89° 10' W., beginning new measurement.

Ascend 95 ft. over SE. slope, through heavy timber and dense undergrowth.

11.55 Top of ascent, slopes S.; desc. 45 ft. over SW. slope.

17.30 Ravine, drains S.; asc. 15 ft. over SE. slope.

19.27 From this point, the NW. cor. of Donation Land Claim No. 48, bears North, 0.26 chs. dist., hereinafter described.

19.35 Woven wire fence, bears N. and S.

19.82 Point for the W 1/16 sec. cor. of secs. 3 and 10.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{S\ 3}{S\ 10}$

1981

from which

A madrone, 9 ins. diam., bears S. 44° W., 46 lks. dist., mkd. W 1/16 S10 BT on bark.