

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines
T. 30 S., R. 4 W., Willamette Meridian, Oregon

16818

CHAINS	A fir, 8 ins. diam., bears N. 21° W., 64 lks. dist., mkd. W 1/16 S3 BT. Ascend 25 ft. over SE. slope. 24.60 Spur, slopes S.; desc. 115 ft. over SW. slope. 32.25 Wet ravine, drains S. 30° W.; asc. 40 ft. over SE. slope. 39.64 The cor. of secs. 3, 4, 9 and 10, perpetuated and recorded by G. G. Stewart, Deputy County Surveyor, in 1922, and further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron pipe, 1/2 in. diam., firmly set, projecting 12 ins. above ground, from which the remaining original bearing trees: A black oak, 20 ins. diam., bears N. 32 1/2° E., 19 lks. dist., with healed double blaze. (record N. 35° E.) A black oak, 36 ins. diam., bears N. 83° W., 59 lks. dist., with healed blaze. (Record, 55 lks.) and bearing trees mkd. by Byron A madrone, 12 ins. diam., bears S. 32° E., 21 lks. dist., with fragmentary scribe marks visible on open blaze. A madrone, 10 ins. diam., bears S. 82° W., 26 lks. dist., with scribe marks W S9 CS BT visible on open blaze. At the corner point Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 30 S R 4 W S 4 S 3 S 9 S 10 1981 from which new bearing trees A fir, 6 ins. diam., bears S. 52 1/2° W., 71 1/2 lks. dist., mkd. T30S R4W S9 BT. A fir, 8 ins. diam., bears N. 57° W., 57 lks. dist., mkd T30S R4W S4 BT. Reset iron pipe alongside iron post. Land, mountainous. Soil, rocky clay laom. Timber, fir, hemlock, cedar, maple, oak, chinquapin, madrone, and alder; undergrowth, salal, poison oak, vine maple, rhododendron, hazel, fern, and grasses.
	Dependent Resurvey of a Portion of the Boundaries of Donation Land Claims, No. 48 and No. 49, T. 30 S., R. 4 W., Willamette Meridian, Oregon