

County Surveyor's Record, Douglas County, Oregon

16821

Dependent Resurvey of a Portion of the Boundaries
of Donation Land Claims, No. 48 and No. 49,
T. 30 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

42.78

The NW. cor. of Donation Land Claim No. 48, perpetuated and recorded by F. C. Frear, Deputy County Surveyor, in 1918, further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, and still further perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1972, monumented with an iron pipe, 1/2 in. diam., firmly set, projecting 5 ins. above ground, from which the remains of the original bearing tree:

A black oak snag, 24 ins. diam., bears S. 80° E., 26 lks. dist., with fragmentary scribe marks visible on open blaze.

and the remains of bearing trees mkd. by Byron

A madrone, 9 ins. diam., bears S. 17° E., 21 1/2 lks. dist., with fragmentary scribe marks visible on partially open blaze.

A sawed fir stump, 25 ins. diam., bears S 75° W., 63 lks. dist., no marks visible.

and a bearing tree mkd. by Powell

A madrone, 9 ins. diam., bears N. 39° E., 39 lks. dist., with fragmentary scribe marks visible on partially open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 30 S R 4 W
S 3 | C 48
1981

Reset iron pipe alongside iron post.

From this point, the W 1/16 sec. cor. of secs. 3 and 10, bears S. 65° 30' W., 0.605 chs. dist., hereinbefore described.

Subdivision of Section 23, T. 30 S., R. 4 W.
Willamette Meridian, Oregon

From the 1/4 sec. cor. of secs. 23 and 26.

N. 1° 36' E., on the N. and S. center line of sec. 23.

Descend 510 ft. over broken NW. slope, through heavy timber and dense undergrowth.

17.25 Woven wire fence, extends E. and W., enter pasture land.

19.06 Point for the center S 1/16 sec. cor. of sec. 23.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16 | C S 23
C
1981