

# County Surveyor's Record, Douglas County, Oregon

**16831**

Dependent Resurvey, Portion of Subdivisional Lines  
T. 23 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>The cor. is located on the upper edge of a steep cutbank, 70 lks. N. of Smith Ridge Road, asphalt surface, 25 lks. wide, bears E. and W.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, cedar, hemlock, alder, maple, and madrone; undergrowth, rhododendron, huckleberry, salmonberry, poison oak, salal, and fern.</p>
	<p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0° 13' W., bet. secs. 7 and 8.</p> <p>Asc. 75 ft. over SE. slope, through moderate timber and undergrowth.</p>
1.80	Spur, slopes S. 80° E.; desc. 60 ft. over NE. slope.
4.40	Ravine, drains S. 80° E.; asc. 135 ft. over SE. slope.
8.15	Spur, slopes N. 70° E.; desc. 380 ft. over NE. slope; also edge of timber, extends N. and S. 70° W.
20.90	Ravine, drains N. 30° E.; asc. 10 ft. over SE. slope.
23.80	Top of ascent, slopes E.; desc. 20 ft. over NE. slope.
25.60	Ravine, drains S. 70° E.; asc. 40 ft. over SE. slope.
28.65	Dirt road, 20 lks. wide, bears S. 60° E. and N. 60° W.
31.40	Ravine, drains S. 70° E.; asc. 140 ft. over SE. slope.
39.90	<p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 S R 8 W</p> <p>1/4</p> <p>S 7   S 8</p> <p>1980</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 14 ins. diam., bears N. 42° E., 44 1/2 lks. dist., mkd. 1/4 S8 BT.</p> <p style="margin-left: 40px;">A fir, 10 ins. diam., bears N. 45 1/2° W., 26 1/2 lks. dist., mkd. 1/4 S7 BT.</p> <p>Asc. 45 ft. over SE. slope.</p>
44.95	Spur, slopes S. 30° E.; desc. 860 ft. over N. slope; also edge of timber, extends S. and W.
72.65	Little Camp Creek, 15 lks. wide, course W.; asc. 150 ft. over S. slope.
79.80	<p>The cor. of secs. 5, 6, 7, and 8, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1966, monumented with an iron post, 1 1/2 ins. diam., loosely set, with iron cap mkd. S5 S6 S7 S8, from which the remains of the original bearing trees:</p>