

County Surveyor's Record, Douglas County, Oregon

16833

Dependent Resurvey, Portion of Subdivisional Lines,
T. 23 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
16.90	Top of ascent, slopes S.; desc. 70 ft. over SW. slope.
19.75	Creek, 2 lks. wide, course S. 10° E.; asc. 50 ft. over NE. slope.
21.10	Spur, slopes S.; desc. 25 ft. over SW. slope.
22.80	Bottom of descent, slopes S.; asc. 15 ft. over SE. slope.
27.25	Little Camp Creek Road, asphalt surface, 35 lks. wide, bears N. 50° E. and S. 60° W., incurve; also, top of ascent, slopes S.; desc. 50 ft. over SW. slope.
34.50	Creek, course S. 30° E.; asc. 75 ft. over NE. slope.
38.45	Spur, slopes S. 15° E.; desc. 10 ft. over SW. slope.
39.98	Point for 1/4 sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 S R 8 W 1/4 $\frac{S\ 6}{S\ 7}$ 1980
	from which
	A fir, 23 ins. diam., bears S. 43 3/4° E., 47 lks. dist., mkd. 1/4 S7 BT.
	A fir, 28 ins. diam., bears N. 69° W., 69 lks. dist., mkd. 1/4 S6 BT.
	Desc. 10 ft. over SW. slope.
42.90	Ravine, drains S. 20° E.; asc. 30 ft. over E. slope.
44.25	Spur, slopes S. 20° E.; desc. 15 ft. over SW. slope.
44.65	Ravine, drains S. 20° E.; asc. 25 ft. over NE. slope.
45.25	Spur, slopes S. 50° E.; desc. 20 ft. over SW. slope.
45.80	Creek, 1 lk. wide, course S. 60° E.; asc. 35 ft. over NE. slope.
47.10	Spur, slopes S. 45° E.; desc. 20 ft. over SW. slope.
49.05	Bottom of descent, slopes S.; asc. 105 ft. over SE. slope.
53.95	Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.
60.25	Spur, slopes S. 10° E.; desc. 80 ft. over SW. slope.
62.00	Dirt road, 15 lks. wide, bears N. 40° W. and S. 40° E.
65.55	Ravine, drains S. 20° E.; asc. 175 ft. over SE. slope.
76.95	Spur, slopes S. 15° E.; desc. 15 ft. over SW. slope.
78.50	Ravine, drains S.; asc. 25 ft. over SE. slope.
85.20	Spur, slopes S. 10° W.; desc. 110 ft. over SW. slope.