

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **16834**
T. 23 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
87.50	Dirt road, 15 lks. wide, bears N. 30° W. and S. 55° E., in curve.
89.50	Bottom of descent, slopes S.; asc. 10 ft. over SE. slope.
91.00	Dirt road, 15 lks. wide, bears N. 40° W. and S. 40° E.
91.40	Spur, slopes S. 40° E.; desc. 15 ft. over SW. slope.
91.75	Ravine, drains S. 10° E.; asc. 45 ft. over E. slope.
96.43	Intersect the E. bdy. of T. 23 S., R. 9 W., true point for the cor. of secs. 6 and 7 only. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center; margin: 10px 0;"> T 23 S R 23 S R 9 W $\frac{S 6}{S 7}$ S 12 R 8 W 1980 </div> from which A hemlock, 18 ins. diam., bears N. 37° E., 71 lks. dist., mkd. T23S R8W S6 BT. A hemlock, 17 ins. diam., bears S. 72 1/2° E., 14 1/2 lks. dist., mkd. T23S R8W S7 BT. From this point, the cor. of secs. 1 and 12 only, T. 23 S., R. 9 W., bears N. 0° 15' E., 14.56 chs. dist., described in the field notes of the dependent resurvey of a portion of the E. bdy. of T. 23 S., R. 9 W., executed concurrently under Group No. 1074 and this same group. Asc. 5 ft. over E. slope.
96.55	The original cor. of secs. 6 and 7 only, monumented with a steel fence post, firmly set, projecting 26 ins. above ground, from which the remains of the original bearing trees: A fir stump, 33 ins. diam., bears N. 70° E., 66 1/2 lks. dist., with healed blaze. (Record and to face. 64 lks.) A fir, 49 ins. diam., bears N. 2° W., 100 lks. dist., with healed blaze. Land, mountainous. Soil, clay loam. Timber, fir, hemlock, cedar, alder, maple, and willow; undergrowth, rhododendron, vine maple, hazel, ocean spray, scotch broom, salal, fer, and swamp grass.
	The point for the N. 1/16 sec. cor. of sec. 6 only, T. 23 S., R. 8 W., is at proportionate dist. on the W. bdy. of sec. 6. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center; margin: 10px 0;"> N 1/16 S 6 1980 </div>