

County Surveyor's Record, Douglas County, Oregon

16835 Dependent Resurvey, Portion of Subdivisional Lines,
T. 23 S., R. 8 W., Willamette Meridian, Oregon

CHAINS																						
	<p>from which</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears N. 46° E., 32 1/2 lks. dist., mkd. N. 1/16 S6 BT.</p> <p style="margin-left: 40px;">A fir, 6 ins. diam., bears S. 35 1/4° E., 47 lks. dist., mkd. X BT.</p> <p>From this point, the true point for the NW. cor. of T. 23 S., R. 8 W., bears N. 0° 27' E., 22.19 chs. dist., described in the field notes of the dependent resurvey of a portion of the E. bdy. of T. 23 S., R. 9 W., executed concurrently under Group No. 1074, and this same group.</p>																					
	<p>From the 1/4 sec. cor. of secs. 5 and 6, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td></td><td style="text-align: center;">1/4</td><td></td></tr> <tr><td></td><td style="text-align: center;">S 6 S 5</td><td></td></tr> <tr><td style="text-align: center;">T 23 S</td><td style="text-align: center;"> </td><td style="text-align: center;">R 8 W</td></tr> <tr><td></td><td style="text-align: center;">1970</td><td></td></tr> </table> </div> <p>from which the remains of an original bearing tree</p> <p style="margin-left: 40px;">A cedar snag, 36 ins. diam., bears N. 42° E., 130 lks. dist., no marks visible on opened blaze.</p> <p>and bearing trees mkd. by Jelley, in 1970</p> <p style="margin-left: 40px;">A fir, 16 ins. diam., bears N. 38 1/4° E., 62 1/2 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 24 ins. diam., bears N. 65° W., 34 1/2 lks. dist., with healed blaze. (Record, 35 1/2 lks.)</p> <p>and bearing trees mkd. by person(s) unknown.</p> <p style="margin-left: 40px;">A fir, 12 ins. diam., bears N. 2 1/2° E., 16 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 16 ins. diam., bears N. 57 3/4° W., 23 lks. dist., with healed blaze.</p> <p>N. 0° 08' E., bet. secs. 5 and 6.</p> <p>Desc. 95 ft. over N. slope, through moderate timber and undergrowth.</p> <p>3.70 Creek, 1 lk. wide, course N. 70° E.; asc. 65 ft. over SE. slope.</p> <p>8.95 Spur, slopes S. 50° E.; desc. 140 ft. over NE. slope.</p> <p>11.65 Creek, 1 lk. wide, course S. 80° E.; asc. 90 ft. over SE. slope.</p> <p>19.93 Point for the N. 1/16 sec. cor. of secs. 5 and 6.</p> <p style="margin-left: 40px;">Set an iron post, 24 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td></td><td style="text-align: center;">N 1/16</td><td></td></tr> <tr><td></td><td style="text-align: center;">S 6 S 5</td><td></td></tr> <tr><td></td><td style="text-align: center;">1980</td><td></td></tr> </table> </div> <p>from which</p>		1/4			S 6 S 5		T 23 S		R 8 W		1970			N 1/16			S 6 S 5			1980	
	1/4																					
	S 6 S 5																					
T 23 S		R 8 W																				
	1970																					
	N 1/16																					
	S 6 S 5																					
	1980																					