

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines **16836**
T. 23 S., R. 8 W., Willamette Meridian, Oregon

| CHAINS | |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | <p>A fir, 20 ins. diam., bears S. 57 1/2° E., 17 lks. dist., mkd. N. 1/16 S5 BT.</p> <p>A fir, 15 ins. diam., bears S. 24 3/4° W., 48 lks. dist., mkd. N 1/16 S6 BT.</p> <p>Set a steel fence post, 5 ft. long, alongside iron post.</p> <p>Asc. 100 ft. over SE. slope.</p> |
| 28.60 | Spur, slopes S. 80° E.; desc. 155 ft. over NE. slope. |
| 33.40 | Creek, 1 lk. wide, course S. 50° E.; asc. 60 ft. over SE. slope. |
| 38.55 | Top of ascent, slopes SE.; desc. 15 ft. over NE. slope. |
| 41.20 | Bottom of descent, slopes SE.; asc. 70 ft. over SE. slope. |
| 43.22 | Intersect the S. bdy. of T. 22 S., R. 8 W., (Fifth Standard Parallel South). |
| | <p>The closing cor. of secs. 5 and 6, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1963, redescribed by Floyd A. Brooks and James E. Jelley in 1963-65, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> |
| | <p>COUNTY SURVEYORS OFFICE T 22 S CC S 6 S 5 T 23 S R 8 W 1963</p> |
| | <p>from which the remaining original bearing trees</p> <p>A fir, 38 ins. diam., bears S. 22 1/2° W., 41 lks. dist., with healed blaze.</p> <p>A fir, 60 ins. diam., bears N. 36° W., 60 lks. dist., with healed blaze. (Record N. 42 1/2° W.)</p> <p>and a bearing tree mkd. by Godfrey</p> <p>A fir, 13 ins. diam., bears S. 75 1/2° E., 41 lks. dist., with healed blaze.</p> |
| | <p>From this point, a local cor. recorded by Brooks and Jelley, in 1963-65, monumented with an iron post, 1 1/2 ins diam., firmly set, projecting 15 ins. above ground, with iron cap mkd. S5 S6 S32, bears East, 0.05 chs. dist.</p> <p>From this same point, the cor. of secs. 31 and 32 only, T. 22 S., R. 8 W., bears N. 89° 37' W., 1.47 chs. dist., described in the field notes of the dependent resurvey of a portion of the S. bdy. of T. 22 S., R. 8 W. (Fifth Standard Parallel South), executed concurrently under this same group.</p> |
| | <p>The point for the 1/4 sec. cor. of sec. 6 only, T. 23 S., R. 8 W., is at proportionate dist. on the N. bdy. of sec. 6.</p> |