

# County Surveyor's Record, Douglas County, Oregon

16837

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon

**CHAINS**

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 S R 8 W  
1/4 S 6  
T 23 S R 8 W  
1980

from which

A fir, 5 ins. diam., bears S. 59 1/4° E., 11 lks. dist., mkd. X BT.

A fir, 8 ins. diam., bears S. 46 1/2° W., 123 1/2 lks. dist., mkd. 1/4 S6 BT.

From this point, the 1/4 sec. cor. of sec. 31 only, T. 22 S., R. 8 W., bears N. 89° 59' W., 1.42 chs. dist., described in the field notes of the dependent resurvey of a portion of the S. bdy. of T. 22 S., R. 8 W. (Fifth Standard Parallel South), executed concurrently under this same group.

The point for the E. 1/16 sec. cor. of sec. 6 only, T. 23 S., R. 8 W., is at midpoint on the N. bdy. of sec. 6 between the 1/4 sec. cor. of sec. 6 only and the closing cor. of secs. 5 and 6.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16  
S 6  
1980

from which

A hemlock, 6 ins. diam., bears S. 32 1/2° E., 78 lks. dist., mkd. E 1/16 S6 BT.

A fir, 19 ins. diam., bears S. 57 1/4° W., 47 1/2 lks. dist., mkd. E 1/16 S6 BT.

Set a steel fence post, 5 ft. long, alongside iron post.

From this point, the cor. of secs. 31 and 32 only, T. 22 S., R. 8 W., bears S. 89° 59' E., 18.30 chs. dist., described in the field notes of the dependent resurvey of a portion of the S. bdy. of T. 22 S., R. 8 W. (Fifth Standard Parallel South), executed concurrently under this same group.

The point for the 80 1/16 sec. cor. of sec. 6 only, T. 23 S., R. 8 W., is at proportionate dist. on the N. bdy. of sec. 6.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

1/16 S 6 80  
1980

from which