

County Surveyor's Record, Douglas County, Oregon

Subdivision of Sec. 6
T. 23 S., R. 8 W., Willamette Meridian, Oregon

16840

CHAINS	
37.20	Ravine, drains N. 5° E.; asc. 75 ft. over NE. slope.
39.74	The center 1/4 sec. cor. of sec. 6. Asc. 95 ft. over NE. slope.
44.50	Spur, slopes N. 5° W.; desc. 30 ft. over NW. slope.
44.90	Bottom of descent, slopes N.; asc. 45 ft. over NE. slope.
50.85	Spur, slopes N. 30° W.; desc. 275 ft. over NW. slope.
58.75	Ravine, drains N. 40° W.; asc. 15 ft. over NE. slope
59.90	Spur, slopes N. 10° W.; desc. 35 ft. over NW. slope.
61.80	Ravine, drains N. 40° E.; asc. 265 ft. over SE. slope.
68.95	Dirt road, 20 lks. wide, bears N. 30° W., and S. 20° E., in curve.
69.50	Spur, slopes N. 30° E.; desc. 70 ft. over NW. slope.
70.65	Dirt road, bears N. 40° E. and S. 40° W.
73.15	Ravine, drains N. 10° E.; asc. 85 ft. over NE. slope.
75.05	Dirt road, bears N. 30° W. and S. 30° E.
77.15	Spur, slopes N. 30° W.; desc. 110 ft. over W. slope.
79.48	Point for the center 80 1/16 sec. cor. of sec. 6. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in ground, to solid rock, and supported in a mound of stone, 3 ft. base, to top, with brass cap mkd. C $\frac{1/16}{S 6}$ 80 1980 from which A fir, 7 ins. diam., bears S. 51 1/2° W., 25 lks. dist., mkd. C 1/16 S6 80 BT. A fir, 8 ins. diam., bears N. 17° W., 16 1/2 lks. dist., mkd. C 1/16 S6 80 BT. Desc. 315 ft. over W. slope.
89.60	Creek, 1 lk. wide, course N. 50° W.; asc. 125 ft. over NE. slope.
96.23	The true point for the 1/4 sec. cor. of sec. 6 only, on the W. bdy. of the Tp., described in the field notes of the dependent resurvey of a portion of the E. bdy. of T. 23 S., R. 9 W., executed concurrently under this same group and Group No. 1074.
	From the center E. 1/16 sec. cor. of sec. 6. N. 0° 16' E., on the N. and S. center line of the NE 1/4 of sec. 6. Asc. 25 ft. over SE. slope, through moderate timber and undergrowth.