

# County Surveyor's Record, Douglas County, Oregon

**16841**

Subdivision of Sec. 6,  
T. 23 S., R. 8 W. Willamette Meridian, Oregon

CHAINS	
4.80	Spur, slopes S. 60° E.; desc. 55 ft. over NE. slope.
9.90	Bottom of descent, slopes S. 30° E.; asc. 25 ft. over SE. slope.
14.20	Spur, slopes S. 70° E.; desc. 100 ft. over NE. slope.
19.50	Ravine, drains N. 70° E.; asc. 5 ft. over SE. slope.
19.95	Point for the NE. 1/16 sec. cor. of sec. 6, at intersection with the E. and W. center line of the NE 1/4.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">NE 1/16 S 6 1980</div> <p>from which</p> <p style="margin-left: 40px;">A fir, 35 ins. diam., bears S. 3 1/2° E., 22 1/2 lks. dist., mkd. NE 1/16 S6 BT.</p> <p style="margin-left: 40px;">A fir, 28 ins. diam., bears N. 69° W., 22 lks. dist., mkd. NE 1/16 S6 BT.</p> <p>Asc. 190 ft. over broken SE. slope.</p>
35.05	Bridge Road, gravelled, 25 lks. wide, bears N. 15° E. and S. 35° W., in curve.
37.45	Top of ascent, slopes E.; desc. 65 ft. over NE. slope.
40.70	Bridge Road, gravelled, 25 lks. wide, bears N. 20° W. and S. 20° E.
43.03	The E 1/16 sec. cor. of sec. 6 only, on the N. bdy. of the Tp., hereinbefore described.
	From the N 1/16 sec. cor. of secs. 5 and 6.  N. 89° 20' W., on the E. and W. center line of the NE 1/4 of sec. 6.  Asc. 10 ft. over NE. slope, through heavy timber and light undergrowth.
3.15	Top of ascent, slopes SE.; desc. 15 ft. over SW. slope.
6.50	Ravine, drains S. 20° E.; asc. 105 ft. over NE. slope.
11.90	Top of ascent, slopes SE.; desc. 20 ft. over rolling SW. slope.
15.55	Ravine, drains S. 45° E.; asc. 75 ft. over NE. slope.
19.83	The NE. 1/16 sec. cor. of sec. 6.  Asc. 170 ft. over NE. slope.
31.35	Lutzinger Creek Road, gravelled, 25 lks. wide, bears N. and S. 25° E., in curve.
32.50	Spur, slopes N.; desc. 150 ft. over SW. slope.
39.65	The center N 1/16 sec. cor. of sec. 6