

# County Surveyor's Record, Douglas County, Oregon

**16847**

Dependent Resurvey, Portion of The W. Bdy.,  
T. 23 S., R. 8 W., Willamette Meridian, Oregon

CHAINS																			
	Asc. 185 ft. over S. slope.																		
27.65	Spur ridge, bears N. 80° E. and S. 80° W.; also leave logged area, enter moderate timber and undergrowth, edge bears N. 80° E. and S. 80° W.; desc. 375 ft. over N. slope.																		
36.85	Ravine, chains N. 20° W.; desc. 95 ft. over NW. slope.																		
40.55	The S. 1/16 sec. cor. of sec. 13 only, T. 23 S., R. 9 W., monumented with an iron post, 2 1/2 ins. diam., firmly set projecting 6 ins. above ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>S 1/16</td><td> </td><td></td></tr> <tr><td>S 13</td><td> </td><td></td></tr> <tr><td colspan="3">1969</td></tr> </table> </div> <p>from which bearing trees mkd. by Jelley and Steward</p> <p style="margin-left: 40px;">A hemlock, 13 ins. diam., bears S. 25 1/2° W., 30 lks. dist. with fragmentary scribe marks visible on partially healed blaze.</p> <p style="margin-left: 40px;">A cedar, 12 ins. diam., bears N. 89° W., 77 lks. dist., with scribe marks 16 S13 B visible on open blaze.</p>	S 1/16			S 13			1969											
S 1/16																			
S 13																			
1969																			
40.565	The cor. of secs. 18 and 19 only, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="3">SURVEYORS</td></tr> <tr><td colspan="3">T 23 S</td></tr> <tr><td>R</td><td>  S 18</td><td>R</td></tr> <tr><td>9</td><td>  S 19</td><td>8</td></tr> <tr><td>W</td><td> </td><td>W</td></tr> <tr><td colspan="3">1967</td></tr> </table> </div> <p>from which the original bearing trees</p> <p style="margin-left: 40px;">A fir, 72 ins. diam., bears N. 15° E., 28 lks. dist. with healed blaze.</p> <p style="margin-left: 40px;">A cedar, 38 ins. diam., bears S. 75° E., 67 lks. dist., with fragmentary scribe marks visible on open blaze.</p> <p style="margin-left: 40px;">A cedar, 32 ins. diam., bears N. 79° W., 15 lks. dist., no marks visible.</p> <p>and bearing trees mkd. and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1967</p> <p style="margin-left: 40px;">A hemlock, 16 ins. diam., bears N. 75° E., 46 1/2 lks. dist., with scribe marks S R8W visible on partially healed blaze.</p> <p style="margin-left: 40px;">A hemlock, 12 ins. diam., bears S. 59° E., 40 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>Land, mountainous. Soil, clay. Timber, fir, hemlock, cedar, alder, maple, myrtle, madrone, chinquapin, and dogwood; undergrowth, rhododendron huckleberry, vine maple, hazel, arrowwood, salmonberry, wild rose, salal, Oregon grape, and fern.</p>	SURVEYORS			T 23 S			R	S 18	R	9	S 19	8	W		W	1967		
SURVEYORS																			
T 23 S																			
R	S 18	R																	
9	S 19	8																	
W		W																	
1967																			