

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the East Boundary, **16848**  
 T. 23 S., R. 9 W., Willamette Meridian, Oregon

**CHAINS**

(Restoring the survey by William H. Byars, U. S. Deputy Surveyor, in 1878, the resurvey by Williams R. Whipple, U. S. Deputy Surveyor, in 1894, and the resurvey by James E. Jelley and Rolla R. Steward, Cadastral Surveyors, in 1969-70)

From the cor. of secs. 12 and 13 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 23 S	T 23 S
R 9 W	R 8 W
S 12	S 7
S 13	
1969	

F-0-10-13  
810  
1871  
4-4-94

from which the remains of the original bearing trees

A decayed fir stump, size indeterminate, bears N. 9 1/2° E., 45 lks. dist., no marks visible. (Record, N. 12° E.)

A chinquapin clump, bears S. 66° E., 36 lks. dist., no marks remaining.

and a bearing tree of unknown origin, recorded by Jelley and Steward

A fir, 28 ins. diam., bears S. 30° E., 17 lks. dist., with healed blaze.

and bearing trees and a bearing object mkd. by Jelley and Steward

A hemlock, 22 ins. diam., bears S. 81° W., 212 lks. dist., with healed blaze.

A fir, 15 ins. diam., bears N. 13° W., 66 1/2 lks. dist., with healed blaze.

The NE. cor. of Lindy Bridge, bears S. 7 3/4° W., 252 lks. dist. to X chiseled in curb. (Record, S. 11 1/4° W.)

N. 0° 15' E., on the E. bdy. of sec. 12, marking and blazing the true line.

Asc. 170 ft. over SE. slope, through moderate timber and undergrowth.

13.25 Spur, slopes S. 40° E.; desc. 20 ft. over NE. slope.

15.10 Ravine, drains S. 45° E.; asc. 110 ft. over SE. slope.

19.65 Dirt road, 20 lks. wide, bears N. 80° E. and N. 75° W., in a curve.

25.50 True point for the 1/4 sec. cor. of sec. 7 only, T. 23 S., R. 8 W.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 S	
R 9 W	R 8 W
	1/4 S 7
1980	