

County Surveyor's Record, Douglas County, Oregon

16850

Dependent Resurvey, Portion of E. Bdy.,
T. 23 S., R. 9 W., Willamette Meridain, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 S	T 23 S
S 1	R 8 W
S 12	S 6
R 9 W	
1980	

from which new bearing trees

A fir, 6 ins. diam., bears S. 37 3/4° W., 15 lks. dist., mkd. T23S R9W S12 BT.

A hemlock, 13 ins. diam., bears N. 55 1/2° W., 88 lks. dist., mkd. T23S R9W S1 BT.

Set a 5 ft. steel fence post alongside the iron post.

Land, mountainous.

Soil, clay loam.

Timber, fir, hemlock, cedar, alder, chinquapin, myrtle, dogwood; undergrowth, salal, huckleberry, Oregon grape, vine maple, rhododendron, hazel and fern.

N. 0° 27' E., on the E. bdy. of sec. 1.

Asc. 60 ft. over SE. slope, through moderate timber and undergrowth.

1.85 Dirt road, 15 lks. wide, bears N. 75° E. and S. 75° W.

5.85 Spur, slopes N. 80° E.; desc. 355 ft. over NW. slope.

25.27 True point for the 1/4 sec. cor. of sec. 6 only, T. 23 S., R. 8 W.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 23 S	
R 9 W	R 8 W
	1/4 S 6
1980	

from which

A hemlock, 8 ins. diam., bears N. 9 1/2° E., 17 lks. dist., mkd. X BT.

A hemlock, 9 ins. diam., bears S. 48 1/2° E., 40 lks. dist., mkd. 1/4 S6 BT.

From this point, the original 1/4 sec. cor. of sec. 6 only, bears N. 89° 23' W., 0.05 chs. dist., perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1967, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 23 S	
R	R
9 1/4	S 6 8
W	W
1967	