

County Surveyor's Record, Douglas County, Oregon

16851

Dependent Resurvey, Portion of E. Bdy.,
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

from which the remains of the original bearing trees

A fir, 35 ins. diam., bears S. 1° E., 27 lks. dist., with healed blaze.

A decayed hemlock stump, size indeterminate, bears N. 45° W., 27 lks. dist., with old axe marks visible on bark.

and bearing trees mkd. by Tracy

A hemlock, 19 ins. diam., bears N. 47° E., 29 lks. dist., with healed blaze.

A hemlock, 12 ins. diam., bears N. 74. 1/2° E., 16 1/2 lks. dist., with healed blaze.

From this point, a point established by person (s) unknown, bears N. 74° 00' W., 0.06 chs. dist., monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 12 ins. above ground.

The cor. is located on a spur, slopes N. 25° W.

Desc. 210 ft. over steep NE. slope.

29.70 Creek, 1 lk. wide, course N. 50° W.; asc. 55 ft. over SW. slope.

35.45 Top of ascent, slopes W.; desc. 15 ft. over NW. slope.

36.10 Ravine, drains S. 80° W.; asc. 90 ft. over SW. slope.

38.66 Point for the 1/4 sec. cor. of sec. 1 only, at proportionate distance; there is no remaining evidence of the original corner. No permanent monument established.

45.25 Point for the N. 1/16 sec. cor. of sec. 6 only, T. 23 S., R. 8 W., described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 23 S., R. 8 W., executed concurrently under Group No. 1005.

Asc. 95 ft. over SW. slope.

58.70 Spur, slopes N. 75° W.; desc. 180 ft. over NE. slope.

64.45 Ravine, drains N. 70° W.; asc. 20 ft. over SW. slope

67.44 True point for the NW. cor. of T. 23 S., R. 8 W.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

			T 22 S
			R 9 W
			S 36
T 23 S			T 23 S
R 9 W			R 8 W
S 1			S 6

1980

from which

A fir, 4 ins. diam., bears S. 60 1/4° E., 58 lks. dist., mkd. X BT.

A fir, 10 ins. diam., bears S. 23 1/2° E., 44 lks. dist., mkd. T23S R8W S6 BT