

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy.,
T. 23 S., R. 9 W., Willamette Meridian, Oregon

16852

CHAINS

From this point, the original NW. cor. of T. 23 S., R. 8 W., bears S. 89° 51' W., 0.14 chs. dist., perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1963, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 23 S T 22 S R 9 W
R 9 W S

 | 36
 | S 6
S 1 T 23 S
 R 8 W
1963

from which the remains of an original bearing tree

A fir stump, 47 ins. diam., bears N. 40° W., 1 lks. dist., rescribed T23S R9W S1 CS BT by Godfrey.

and a bearing tree mkd. by Godfrey

A fir, 18 ins. diam., bears S. 71° E., 85 lks. dist., with healed blaze.

and a bearing tree mkd. by Vernon R. Tracy, Deputy County Surveyor, in 1966

A fir, 15 ins. diam., bears N. 49° E., 40 lks. dist., with healed blaze.

From this same point, the cor. of Tps. 22 S., Rs. 8 and 9 W., bears N. 89° 51' E., 8.60 chs. dist., described in the field notes of the dependent resurvey of a portion of the S. bdy. (Fifth Standard Parallel South), T. 22 S., R. 8 W., executed concurrently under Group No. 1005

Asc. 120 ft. over broken SW. slope.

78.53

The NE. cor. of T. 23 S., R. 9 W., perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1963, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 15 ins. above ground, from which the remains of the original bearing trees.

A fir stump, 40 ins. diam., bears N. 20° E., 24 lks. dist., no marks visible.

A decaying chinquapin snag, size indeterminate bears S. 70° E., 40 lks. dist., no marks visible.

A roothole, bears S. 50° W., 24 lks. dist., alongside of which is a downed, decayed fir, 30 ins. diam., no marks visible.

A roothole, bears N. 88° W., 29 lks. dist., alongside of which is a downed fir, 32 ins. diam., with illegible scribe marks visible on opened blaze.

and a bearing tree mkd. by Godfrey

A white fir, 20 ins. diam., bears S. 41° E., 47 1/2 lks. dist., with healed blaze.

At the corner point