

# County Surveyor's Record, Douglas County, Oregon

16853

Dependent Resurvey, Portion of E. Bdy.,  
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 22 S	R 9 W
T 23 S	S 36
R 9 W	S 1
1980	

from which a new bearing tree

A fir, 10 ins. diam., bears S. 88 3/4° W., 41 lks. dist., mkd. T23S R9W S1 BT.

Deposit the iron pipe alongside the iron post.

The cor. is located on top of a spur ridge, bears N. 15° W. and S. 15° E.

Land, mountainous.  
Soil, rocky clay.

Timber, fir, hemlock, cedar, alder, maple, myrtle, chinquapin, and dogwood; undergrowth, vine maple, hazel, rhododendron, poison oak, manzanita, arrowwood, salal, and fern.

Dependent Resurvey of a Portion of the North Boundary,  
T. 23 S., R. 9 W., Willamette Meridian, Oregon

(Restoring the survey by William H. Byars, U. S. Deputy Surveyor, in 1878, and the resurvey by Elmer O. Worrick, U. S. Deputy Surveyor, in 1894)

From the cor. of secs. 1 and 2 only, on the N. bdy. of the Tp., perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1968, monumented with an iron pipe, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS

T 22 S	R 9 W	S 2	S 1
T 23 S			
OFFICE 1968			

from which the remains of the original bearing trees

A decayed fir stump, size indeterminate, bears N. 45° E., 10 lks. dist., no marks remaining.

A decayed fir stump, size indeterminate, bears S. 40° E., 7 lks. dist., no marks remaining.

and the remains of a bearing tree mkd. by Worrick

A roothole, bears S. 66° W., 270 lks. dist., with a downed fir alongside, 36 ins. diam., with scribe marks W 17 T23S R9 W visible on open blaze.

and bearing trees mdk. by Tracy

A fir, 18 ins. diam., bears S. 72° E., 12 lks. dist., with healed blaze.

A fir, 10 ins. diam., bears S. 28° W., 30 lks. dist., with healed blaze.