

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of N. Bdy.,
T. 23 S., R. 9 W., Willamette Meridian, Oregon

16854

CHAINS

A fir, 19 ins. diam., bears S. 88 1/2° W., 14 lks. dist., with healed blaze.

N. 89° 47' W., on the N. bdy. of sec. 2, marking and blazing the true line.

Asc. 60 ft. over SE. slope, through moderate timber and undergrowth.

12.40 Ridge, bears N. 40° E. and S. 40° W.; desc. 75 ft. over NW. slope.

13.10 Dirt road, 15 lks. wide, bears N. 40° E. and S. 40° W.

19.88 Point for the E. 1/16 sec. cor. of sec. 2 only.

Set an iron post, 28 ins. long, 2 1/2 ins. diam. 26 ins. in the ground, with brass cap mkd.

E 1/16 S 2
1980

from which

A fir, 23 ins. diam., bears S. 57 1/2° E., 16 lks. dist., mkd. E 1/16 S2 BT.

A maple, 19 ins. diam., bears S 17 3/4° W., 64 lks. dist., mkd. E 1/16 S2 BT.

Desc. 50 ft. over NW. slope.

24.00 Bottom of descent, slopes N. 40° W.; asc. 130 ft. over NE. slope.

28.30 Spur, slopes N.; desc. 20 ft. over NW. slope.

33.60 Bottom of descent, slopes N.; asc. 50 ft. over NE. slope.

38.90 Spur, slopes N.; desc. 10 ft. over NW. slope.

39.76 The 1/4 sec. cor. of sec. 2 only, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1968, monumented with an iron post, 1 1/2 ins. diam., firmly set projecting 18 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS
T 22 S R 9 W 1/4
T 23 S R 9 W 1/4 S 2
OFFICE 1962

from which the remains of the original bearing trees

A fir, 50 ins. diam., bears East, 35 lks. dist., with healed blaze.

A roothole, bears West, 52 lks. dist., with a downed fir alongside, 36 ins. diam., with aze marks visible on opened blaze.

and bearing trees mkd. by Tracy

A fir, 12 ins. diam., bears S. 31 1/2° E., 28 lks. dist., with healed blaze.

A maple, 20 ins. diam., bears S. 89° W., 21 lks. dist., with healed blaze.