

County Surveyor's Record, Douglas County, Oregon

16855

Dependent Resurvey, Portion of N. Bdy.,
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	<p>N. 89° 25' W., beginning new measurement.</p> <p>Desc. 10 ft. over NW. slope.</p> <p>3.60 Bottom of descent, slopes N.; asc. 215 ft. over E. slope.</p> <p>10.50 Spur, slopes S. 20° E.; desc. 130 ft. over SW. slope.</p> <p>20.30 Bottom of descent, slopes S.; asc. 30 ft. over SE. slope.</p> <p>23.30 Spur, slopes S. 40° W.; desc. 340 ft. over W. slope.</p> <p>26.10 Dirt road, 25 lks. wide, bears N. and S. 10° W., in a curve.</p> <p>39.04 The cor. of secs. 2, 3, 34, and 35, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1967, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 14 ins. above ground with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T22S</td> <td style="padding: 0 10px;">R9W</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 34</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 35</td> </tr> <tr> <td style="padding: 0 10px;">T23S</td> <td style="padding: 0 10px;"></td> <td style="border-left: 1px solid black; padding: 0 5px;">S 3</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 2</td> </tr> </table> <p>OFFICE 1967</p> </div> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A fir, 70 ins. diam., bears N. 60° E., 71 lks. dist., with fragmentary scribe marks visible on bark.</p> <p style="margin-left: 40px;">A fir stump, 36 ins. diam., bears S. 20° E., 99 lks. dist., with fragmentary scribe marks visible on open blaze.</p> <p style="margin-left: 40px;">A fir stump, 36 ins. diam., bears S. 50° W., 45 lks. dist., with decayed blaze.</p> <p>and trees mkd. by Tracy in 1967</p> <p style="margin-left: 40px;">A fir, 12 ins. diam., bears N. 49° E., 46 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 24 ins. diam., bears S. 40° E., 60 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A hemlock, 20 ins. diam., bears S. 79° W., 66 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 18 ins. diam. bears N. 55° W., 76 lks. dist., with healed blaze.</p> <p>Land mountainous Soil, clay loam. Timber, fir, cedar, hemlock, madrone, chinquapin, alder, maple, dogwood, oak, willow, and myrtle; undergrowth, vine maple, hazel, arrowwood, huckleberry, th-mbleberry, elderberry, salmonberry, salal, poison oak, Oregon grape, and fern.</p>	T22S	R9W	S 34	S 35	T23S		S 3	S 2
T22S	R9W	S 34	S 35						
T23S		S 3	S 2						
	<p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 S., R. 9 W., Willamette Meridian, Oregon</p>								
	<p>(Restoring the survey by William H. Byars, U. S. Deputy Surveyor, in 1878, and the survey by Oscar F. Thiel, U. S. Deputy Surveyor, in 1898-99)</p>								