

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **16856**
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

From the cor. of secs. 1, 2, 11, and 12, monumented with a 5 ft. steel fence post, firmly set, 24 ins. in the ground, from which the remains of an original bearing tree

A fir stump, 36 ins. diam., bears S. 50° W., 58 lks. dist., with fragmentary scribe marks visible on burned and decayed bark blaze, and remarked RP3 on bark blaze, by person(s) unknown.

and local bearing trees mkd. by person(s) unknown

A fir, 30 ins. diam., bears S. 17 1/4° E., 50 lks. dist., with scribe marks RP 51 visible on bark blaze.

A fir, 30 ins. diam., bears N. 20 1/4° W., 34 lks. dist., with scribe marks RP2 visible on bark blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T	23	S	R	9	W
	S	2		S	1
	S	11		S	12
	1980				

*FD OK
M. Smalley
10/97
M124-64*

from which new bearing trees

A fir, 8 ins. diam., bears N. 78 1/2° E., 50 lks. dist., mkd. T23S R9W S1 BT.

A fir, 8 ins. diam., bears S. 41 3/4° W, 107 lks. dist., mkd. T23S R9W S11 BT.

Reset the fence post alongside the iron post.

N. 1° 22' W., bet. secs. 1 and 2, marking and blazing the true line.

Asc. 45 ft. along W. slope, through moderate timber and undergrowth.

3.20 Spur, slopes S. 40° W.; desc. 30 ft. over NW. slope.

6.60 Ravine, drains S. 60° W.; asc. 60 ft. over SW. slope.

9.40 Spur, slopes W.; desc. 40 ft. over NW. slope.

19.50 Ravine, drains S. 80° W.; asc. 320 ft. over SW. slope.

35.25 Dirt road, 15 lks. wide, bears N. 80° E. and S. 80° W.

39.33 The 1/4 sec. cor. of secs. 1 and 2, determined from the remains of an original bearing tree

A fir stump, 50 ins. diam., bears S. 80° W., 50 lks. dist., with fragmentary scribe marks visible on bark blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.