

County Surveyor's Record, Douglas County, Oregon

16857

Dependent Resurvey, Position of Subdivisional Lines,
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	T 23 S R 9 W 1/4 S 2 S 1 1980
	from which new bearing trees
	A fir, 9 ins. diam., bears N. 65° E., 30 lks. dist., mkd. 1/4 S1 BT.
	A fir, 9 ins. diam., bears S. 56-1/4° W., 28 lks. dist., mkd. 1/4 S2 BT.
	From this point, a local cor. established by person(s) unknown, bears N. 80° 00' E., 0.045 chs. dist., monument- ed with an iron pipe, firmly set, projecting 12 ins. above ground, with brass cap mkd. 1/4 S1 1/4 S2.
	<hr style="width: 20%; margin: 0 auto;"/>
	N. 0° 46' W., beginning new measurement
	Asc. 70 ft. over SW. slope.
3.60	Ridge, bears N. 55° W. and S. 55° E.; desc. 335 ft. over broken NE. slope.
14.20	Creek, 2 lks. wide, course N. 65° E.; asc. 145 ft. over SE. slope.
19.955	Point for the N. 1/16 sec. cor. of secs. 1 and 2. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	N 1/16 S 2 S 1 1980
	from which
	A fir, 13, ins. diam., bears S. 16-1/4° E., 23 lks. dist., mkd. N 1/16 S1 BT.
	A fir, 14 ins. diam., bears N. 20-1/4° W., 18 lks. dist., mkd. N 1/16 S2 BT.
	The cor. is located on spur, slopes N. 45° E.
	Desc. 200 ft. over NE. slope.
25.90	Creek, 1 lk. wide, course E.; asc. 165 ft. over SE. slope.
33.70	Spur, slopes S. 55° E.; desc. 90 ft. over NE. slope.
36.75	Creek, 3 lks. wide, course S. 70° E.; asc. 200 ft. over SE. slope.
40.06	The cor. of secs. 1 and 2 only, on the N. bdy. of the Tp.
	Land, mountainous. Soil, clay loam. Timber, fir, hemlock, cedar, alder, maple, chinquapin, myrtle, madrone, dogwood, and yew; undergrowth, vine maple, hazel, arrowwood, huckleberry, salmonberry, thimbleberry, blackberry, manzanita, Oregon grape, salal, poison oak, and fern.