

# County Surveyor's Record, Douglas County, Oregon

16858

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAINS							
	<p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>N. 89° 22' W., bet. secs. 2 and 11.</p> <p>Desc. 205 ft. over SW. slope, through moderate timber and dense undergrowth.</p>						
9.20	<p>Camp Creek Road, asphalt surface, 40 lks. wide, bears N. 20° W. and S. 20° E.</p>						
18.20	<p>Camp Creek, 25 lks. wide, course N. 15° W.; asc. 255 ft. over NE. slope.</p>						
23.40	<p>Spur, slopes N.; desc. 140 ft. over NW. slope.</p>						
32.52	<p>Camp Creek, 25 lks. wide, course S. 70° E.; asc. 5 ft. over nearly level land, along creek bottom.</p>						
39.01	<p>Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2-1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 S R 9 W</p> <p>1/4 <math>\frac{S \ 2}{S \ 11}</math></p> <p>1980</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 38 ins. diam., bears S. 47° E., 66 lks. dist., mkd. 1/4 S11 BT.</p> <p style="margin-left: 40px;">A fir, 28 ins. diam., bears N. 42-1/4° W., 45 lks. dist., mkd. 1/4 S2 BT.</p> <p>Desc. 15 ft. over nearly level land, along creek bottom.</p>						
48.10	<p>Otter Creek Road, asphalt surface, 30 lks. wide, bears N. and S.</p>						
50.40	<p>Enter Camp Creek, 25 lks. wide, course W. from S. 80° E.</p>						
54.20	<p>Waterfall, 25 ft. high, faces W., on Camp Creek; desc. 25 ft. along creek bottom.</p>						
57.40	<p>Leave Camp Creek, course S. 75° W.; continue along bottom land.</p>						
59.80	<p>Otter Creek, 20 lks. wide, course N.; asc. 380 ft. over NE. slope.</p>						
72.60	<p>Spur, slopes N. 20° E.; asc. 70 ft. over broken SE. slope.</p>						
78.02	<p>The cor. of secs. 2, 3, 10, and 11, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1969, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T23S</td> <td style="padding: 0 10px;">R9W</td> <td style="padding: 0 10px;"><math>\frac{S \ 3   S \ 2}{S \ 10   S \ 11}</math></td> </tr> <tr> <td style="padding: 0 10px;">OFFICE</td> <td style="padding: 0 10px;"></td> <td style="padding: 0 10px;">1969</td> </tr> </table> </div> <p>from which the remains of an original bearing tree</p>	T23S	R9W	$\frac{S \ 3   S \ 2}{S \ 10   S \ 11}$	OFFICE		1969
T23S	R9W	$\frac{S \ 3   S \ 2}{S \ 10   S \ 11}$					
OFFICE		1969					