

County Surveyor's Record, Douglas County, Oregon

16859

Dependent Resurvey, Portion of Subdivisional Lines,
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

A maple, 22 ins. diam., bears N. 89° E., 44 lks. dist., with healed blaze.

and bearing trees mkd. by Thiel

A maple, 12 ins. diam., bears S. 89 1/2° W., 30 lks. dist., with healed blaze.

A maple, 13 ins. diam., bears N. 75° W., 24 lks. dist., with healed blaze.

and bearing trees mkd. by Tracy

A hemlock, 12 ins. diam., bears S. 88° E., 12 lks. dist., with healed blaze.

A fir, 18 ins. diam., bears S. 25° W., 33 lks. dist., with healed blaze.

A hemlock, 9 ins. diam., bears N. 31° W., 67 lks. dist., with healed blaze.

Land, mountainous.

Soil, clay loam.

Timber, fir, cedar, hemlock, madrone, myrtle, alder, maple, chinquapin, dogwood, willow, and yew; undergrowth, vine maple, hazel, huckleberry, arrowwood, salal, Oregon grape, manzanita, poison oak, blackberry, salmonberry, and fern.

N. 1° 34' W., bet. secs. 2 and 3.

Asc. 65 ft. over SE. slope, through moderate timber and undergrowth.

3.60 Spur, slopes NE.; desc. 560 ft. over broken NE. slope.

39.44 The 1/4 sec. cor. of secs. 2 and 3, reestablished and recorded by Ronald E. Stuntzner, RLS No. 1342, in 1980, and is accepted as the best available evidence of the position of the original cor., monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

T 23 S R 9 W
1/4
S 3 | S 2
1980

from which bearing trees mkd. by Stuntzner

A fir, 36 ins. diam., bears N. 34° E., 34 lks. dist., with scribe marks 1/4 S3 BT visible on open blaze.

A fir, 42 ins. diam., bears S. 74° E., 44 lks. dist., with scribe marks 1/4 S2 BT visible on open blaze.

and a new bearing tree

A fir, 30 ins. diam., bears N. 57 1/2° W., 65 lks. dist., mkd. 1/4 S3 BT.

N. 1° 34' W., beginning new measurement.

Desc. 85 ft. over N. slope.