

# County Surveyor's Record, Douglas County, Oregon

16860

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
8.50	Camp Creek, 50 lks. wide, course N. 55° W.; asc. 400 ft. over broken SW. slope.
10.40	Camp Creek Road, asphalt surface, 40 lks. wide, bears N. 55° W. and S. 55° E.
91.40	Spur, slopes W.; desc. 35 ft. over NW. slope.
39.69	The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp.  Land, mountainous. Soil, clay. Timber, fir, cedar, hemlock, alder, maple, madrone, myrtle, chinquapin, dogwood, and yew; undergrowth, vine maple, hazel, arrowwood, huckleberry, thimbleberry, blackberry, salmonberry, poison oak, salal, Oregon grape and fern.
Subdivision of Section 2, T. 23 S., R. 9 W., Willamette Meridian, Oregon	
	From the 1/4 sec. cor. of secs. 2 and 11. N. 1° 36' W., on the N. and S. center line of sec. 2.  Asc. 125 ft. over SW. slope, through moderate timber and dense undergrowth.
15.10	Camp Creek Road, asphalt surface, 40 lks. wide, bears N. 80° E. and N. 80° W. in curve,
39.41	Point for the center 1/4 sec. cor. of sec. 2, at intersection with the E. and W. center line.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  T 23 S R 9 W C 1/4 S 2 1982  from which  A fir, 17 ins. diam., bears N. 58 1/4° E., 18 lks. dist., mkd. C 1/4 S2 BT.  A fir, 13 ins. diam., bears S. 79 1/4° W., 10 lks. dist., mkd. X BT.  Asc. 25 ft. over SW. slope.
46.65	Top of ascent, slopes W.; desc. 15 ft. over NW. slope.
48.15	Draw, drains SW.; asc. 65 ft. over SW. slope.
56.85	Creek, 2 lks. wide, course SW.; asc. 90 ft. over SW. slope.
59.20	Point for the center N. 1/16 sec. cor. of sec. 2.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.