

County Surveyor's Record, Douglas County, Oregon

16861

Subdivision, Sec. 2,
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	$\begin{array}{c} \text{C} \\ \text{N } 1/16 \quad \quad \text{S } 2 \\ \text{C} \\ 1982 \end{array}$
	<p>from which</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 79 1/4° E., 17 1/2 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears West., 25 lks. dist., mkd. CN 1/16 S2 BT.</p> <p>Asc. 330 ft. over SW. slope.</p>
70.40	Dirt road, 20 lks. wide, bears N. 70° W., and S. 70° E.
73.60	Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W.
76.20	Top of ascent, slopes W.; desc. 60 ft. over N. slope.
79.19	The 1/4 sec. cor. of sec. 2 only, on the N. bdy. of the Tp.
	<p>From the 1/4 sec. cor. of secs. 1 and 2.</p> <p>N. 89° 18' W., on the E. and W. center line of sec. 2.</p> <p>Desc. 60 ft. over SW. slope, through moderate timber and undergrowth.</p>
19.61	<p>Point for the center E. 1/16 sec. cor. of sec. 2.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	$\begin{array}{c} \text{C} \quad \frac{\text{E } 1/16}{\text{S } 2} \quad \text{C} \\ 1982 \end{array}$
	<p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 51 1/2° W., 27 lks. dist., mkd. CE 1/16 S2 BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 35° W., 24 1/2 lks. dist., mkd. X BT.</p> <p>Desc. 340 ft. over SW. slope.</p>
24.85	Dirt road, 20 lks. wide, bears N. 30° W. and S. 30° E.
39.22	The center 1/4 sec. cor. of sec. 2.
	Desc. 160 ft. over SW. slope.
52.55	Camp Creek Road, asphalt surface, 40 lks. wide, bears N. and S. 30° W. in curve.
58.90	Camp Creek, 70 lks. wide, course N. 10° W.; asc. 5 ft. along broken N. slope.
78.26	The 1/4 sec. cor. of secs. 2 and 3.
	<p>From the center E. 1/16 sec. cor. of sec. 2.</p> <p>N. 1° 11' W., on the N. and S. center line of the NE 1/4 of sec. 2.</p>