


# County Surveyor's Record, Douglas County, Oregon

16863

Subdivision, Sec. 13,  
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A fir snag, 30 ins. diam., bears N. 65° E., 26 lks. dist., no marks visible.</p> <p style="margin-left: 40px;">A roothole, bears S. 62-1/2° W., 14 lks. dist., with a downed cedar alongside, 20 ins. diam., with scribe marks /4S visible on burned blaze.</p> <p>and bearing trees mkd by Tracy</p> <p style="margin-left: 40px;">A hemlock, 15 ins. diam., bears S. 28° W., 26 lks. dist., with scribe marks S24 CS visible on partially healed blaze.</p> <p style="margin-left: 40px;">A hemlock, 18 ins. diam., bears N. 23° W., 19-1/2 lks. dist., with scribe marks S13 CS B visible on partially healed blaze.</p> <p>and a reference monument established by George C. and Crystal M. Barton, in 1966</p> <p style="margin-left: 40px;">An iron pipe, 1/2 in. diam., bears S. 53° W., 1 lk. dist., with a 1/4 in. thick, rectangular metal plate, 12 x 7 ins., affixed to top, mkd.</p> <p style="text-align: center; margin-left: 100px;">T 23 S R 9 W N 1/4 Sec. 24 established 6-6-66 George C. Barton Crystal M. Barton</p> <p style="margin-left: 40px;">N. 0° 28' W., on the N. and S. center line of sec.13.</p> <p style="margin-left: 40px;">Asc. 40 ft. over SW. slope, through moderate timber and undergrowth.</p>
4.35	Spur, slopes S. 75° W.; desc. 185 ft. over NW. slope.
17.50	Road, asphalt surface, 25 lks. wide, bears N. 70° E. and S. 70° W.
18.20	Camp Creek, 20 lks. wide, course N. 70° E.; continue along nearly level bottom land.
19.74	Point for the center S. 1/16 sec. cor. of sec. 13.
	<p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center; margin-left: 100px;">  </p>
	<p>from which</p> <p style="margin-left: 40px;">A fir, 52 ins. diam., bears S. 3° E., 23 lks. dist., mkd. C 1/16 S13 BT.</p> <p style="margin-left: 40px;">A fir, 26 ins. diam., bears N. 58 1/2° W., 42 lks. dist., mkd. CS 1/16 S13 BT.</p> <p>Continue over nearly level land.</p>
39.48	Point for the center 1/4 sec. cor. of sec. 13, at intersec- tion with the E. and W. center line.