

# County Surveyor's Record, Douglas County, Oregon

16864

Subdivision, Sec. 13,  
T. 23 S., R. 9 W., Willamette Meridian, Oregon

**CHAINS**

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.

T 23 S R 9 W  
C 1/4 S 13  
1981

from which

A hemlock, 15 ins. diam., bears S. 64° E., 62 lks. dist., mkd. C 1/4 S13 BT.

A fir, 18 ins. diam., bears N. 64° W., 71 lks. dist., mkd. C 1/4 S13 BT.

Asc. 10 ft. over nearly level land.

59.435 Point for the center N. 1/16 sec. cor. of sec. 13.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.

C  
N 1/16 | S 13  
C  
1981

from which

A hemlock, 35 ins. diam., bears N. 89 1/4° E., 26 lks. dist., mkd. CN 1/16 S13 BT.

A fir, 16 ins. diam., bears S. 44 1/2° W., 75 lks. dist., mkd. CN 1/16 S13 BT.

Desc. 25 ft. over NE. slope.

67.25 Creek, 1 lk. wide, course S. 70° E.; asc. 280 ft. over SE. slope.

80.90 Road, asphalt surface, 25 lks. wide, bears N. 70° W. and E., in curve.

110.15 Spur, slopes N. 80° E.; desc. 65 ft. over N. slope.

114.38 The 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 23 S R 9 W  
1/4  $\frac{S 12}{S 13}$   
1969

from which the remaining original bearing tree

A fir, 62 ins. diam., bears N. 50° E., 47 lks. dist., no marks visible on opened blaze.

and a bearing tree mkd. by Jelley and Steward in 1969-70

A hemlock, 24 ins. diam., bears S. 78° E., 45 1/2 lks. dist., with healed blaze

From the 1/4 sec. cor. of sec. 13 only, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.