

# County Surveyor's Record, Douglas County, Oregon

16865

Subdivision, Sec. 13,  
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	T 23 S R 9 W 1/4 S 13 1969
	from which bearing trees mkd. by Jelley and Steward  A hemlock, 35 ins. diam., bears S. 9 3/4° W., 51 lks. dist., with scribe marks S13 BT visible on open blaze.  A hemlock, 11 ins. diam., bears N. 28 1/4° W., 47 lks. dist., with healed blaze.  N 89° 37' W., on the E. and W. center line of sec. 13.  Asc. 105 ft. over NE. slope, through moderate timber and undergrowth.
7.65	Spur, slopes N. 50° W.; desc. 50 ft. over SW. slope.
18.735	Point for the center E. 1/16 sec. cor. of sec. 13.  Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.  <div style="text-align: center;"> <math display="block">\begin{array}{ccc} &amp; \text{E } 1/16 &amp; \\ \text{C} &amp; \frac{\quad}{\text{S } 13} &amp; \text{C} \\ &amp; 1981 &amp; \end{array}</math> </div>
	from which  A hemlock, 32 ins. diam., bears N. 63° E., 22 lks. dist., mkd. CE 1/16 S13 BT.  A fir, 28 ins. diam., bears N. 18° W., 50 lks. dist., mkd. CE 1/16 S13 BT.  Desc. 10 ft. over broken W. slope.
18.85	Creek, 1 lk. wide, course N. 40° W. from S. 80° E.; desc. 60 ft. over broken W. slope.
29.10	Creek, 1 lk. wide, course S. 20° W.; desc. 10 ft. over broken W. slope.
30.05	Camp Creek Road, asphalt surface, 25 lks. wide, bears N. 15° E. and S. 15° W.
37.15	Camp Creek, 20 lks. wide, course N. 20° W.; asc. 15 ft. over nearly level land.
38.32	The center 1/4 sec. cor. of sec. 13.  Asc. 225 ft. over broken SE, slope.
57.965	Point for the center W. 1/16 sec. cor. of sec. 13.  Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.  <div style="text-align: center;"> <math display="block">\begin{array}{ccc} &amp; \text{W } 1/16 &amp; \\ \text{C} &amp; \frac{\quad}{\text{S } 13} &amp; \text{C} \\ &amp; 1981 &amp; \end{array}</math> </div>
	from which