

County Surveyor's Record, Douglas County, Oregon

16866

Subdivision, Sec. 13,
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 12 ins. diam., bears S. 8 1/2° E., 51 lks. dist., mkd CW 1/15 S13 BT.</p> <p>A fir stump, 34 ins. diam., bears N. 78° W., 27 lks. dist., mkd. CW 1/16 S13 BT.</p> <p>The cor. is located at E. edge of logged area, edge bears N. and S.</p> <p>Asc. 10 ft. over broken SE. slope, through logged area.</p>
77.61	<p>The 1/4 sec. cor. of secs. 13 and 14, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 S R 9 W</p> <p>1/4</p> <p>S 14 S 13</p> <p>1969</p> </div> <p>from which the original bearing trees</p> <p>A maple, 26 ins. diam., bears N. 87 1/2° E., 40 lks. dist., with healed blaze.</p> <p>A fir, 57 ins. diam., bears N. 77° W., 41 lks. dist., with healed blaze.</p>
	<p>From the center E. 1/16 sec. cor. of sec. 13.</p> <p>N. 0° 32' W., on the N. and S. center line of the NE 1/4 of sec. 13.</p> <p>Asc. 185 ft. over SW. slope, through moderate timber and undergrowth.</p>
8.60	<p>Spur, slopes N. 45° W.; desd. 220 ft. over broken N. slope.</p>
14.45	<p>Creek, 4 lks. wide, course N. 65° W.; asc. 30 ft. over SW. slope.</p>
16.33	<p>Graveled road, 18 lks. wide, bears N. 55° W. and S. 55° E.</p>
18.60	<p>Spur, slopes W.; desc. 35 ft. over NW. slope.</p>
20.00	<p>Point for the NE. 1/16 sec. cor. of sec. 13, at intersection with the E. and W. center line of the NE 1/4.</p> <p>Position is occupied by a maple, 16 ins. diam., mkd. NE 1/16 S13 on N. face.</p> <p>from which</p> <p>A fir, 14 ins. diam., bears N. 86 1/2° W., 45 lks. dist., mkd. NE 1/16 S13 BT.</p> <p>An aluminum post, 28 ins. long, 2 1/4 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 56° E., 9 lks. dist., with aluminum cap mkd. NE 1/16 S13 RM 1981 with an arrow pointing to the corner.</p> <p>Desc. 55 ft. over NW. slope.</p>